
#### Systeme - Lineare Elemente | Modular 65013



Technische Daten				
Тур				
Installationsposition	Decke			
Installationsumgebung	Indoor			
IK	IK08			
Glühdrahtprüfung	850°			
Direkte Montage auf normal entflammbaren Oberflächen	Ja			
CE	Ja			
Leuchte dimmbar	Nein			
Schwenkbarkeit	Nein			
Drehbarkeit	Nein			
Begehbarkeit	Nein			
Überrollbarkeit	Nein			
Einschließlich Kabel	Nein			
Harzbeschichtung	Nein			
Nettogewicht	3.02 Kg			
Modularity	Modular			



Oberfläche Gehäuse			
Material	Aluminium		
Farbe	Kreideweiß		
Bearbeitungstyp	Lackierung		

#### 

Systeme - Lineare Elemente | Modular 65013

Components			
D D D D D D D D D D D D D D D D D D D		Ribbon PRO - topLED 18 W DC - 18 W AC	Code 82123
D D D D D D D D D D D	5000 	Ribbon PRO - LED Strip   topLED 18 W DC 24 V   3.6 W/m   518 Lm/m	<b>Code</b> 82124
<mark>6 6∛8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 </mark>	5000 	Ribbon PRO	<b>Code</b> 82125
6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6		Ribbon PRO - LED Strip   topLED 48 W DC 24 V   9.6 W/m   1367 Lm/m	<b>Code</b> 82129
⊕ <mark>n B</mark> ∎B B <mark>a</mark> B Base and a s <b>B</b> ase	5000 	Ribbon PRO	<b>Code</b> 82130
ard a a <mark>a</mark> a a <mark>aa a a</mark> a a		Ribbon PRO - LED Strip   topLED 48 W DC 24 V   9.6 W/m   1503.8 Lm/m	<b>Code</b> 82131
a a <b>fan a a ain a ain a a</b> fan a a	5000 	Ribbon PRO - LED Strip   topLED 33.5 W DC 24 V   6.7 W/m   927.6 Lm/m	<b>Code</b> 82156
ិត ភ្នំតិសំ ឆ <b>ង</b> ភ្នំតែ ភ្នំត្រ ភ្		Ribbon PRO	<b>Code</b> 82157

#### Systeme - Lineare Elemente | Modular 65013

Components 5000 Code Ribbon PRO 82158 n á þá niu ája n á þa ni 62.5 × adve 5000 Code Ribbon PRO 82162 n á þá niu ája n á þa ni \_\_\_\_\_\_ 62.5 × -----Code 5000 Ribbon PRO 82164 n na na na na na na na \_\_\_\_\_ 62.5 × an lost 5000 Code Ribbon PRO - LED Strip | topLED 68 W DC 24 V | 13.6 W/m | 82163 n na na na na na na n 1961.2 Lm/m 62.5 × and set Code Ribbon PRO - LED Strip | topLED 84 W DC 24 V | 16.8 W/m | 82168 2371.4 Lm/m powerer and an and a second and a second a secon 50 × -----5000 1 Code 82169 Ribbon PRO - LED Strip | topLED 84 W DC 24 V | 16.8 W/m | 2419.6 Lm/m \_\_\_\_\_powerer(powerstreen) | 10 50 × and we Code 5000 82170 Ribbon PRO - LED Strip | topLED 84 W DC 24 V | 16.8 W/m | прожессированирован разменона 10 2602.6 Lm/m 50 × and the second 5000 1 Code C00423WH Ribbon PRO - LED Strip | topLED 43 W DC 48 V | 8.6 W/m | \*\*\*\* 1296.4 Lm/m 125

Systeme - Lineare Elemente | Modular 65013

Components 5000 Code Ribbon Plus 82174 D. B. B DORD D 100 1 5000 Code Ribbon Plus - LED Strip | topLED 24 W DC 24 V | 4.8 W/m | 82175 D.B.B DORD D 586 Lm/m -----100 -X + 5000 1 Code Ribbon Plus - LED Strip | topLED 24 W DC 24 V | 4.8 W/m | 82176 D.B.B DOLD D 622 Lm/m 100 -X 1 5000 Code Ribbon Plus - LED Strip | topLED 48 W DC 24 V | 9.6 W/m | 82180 D.B.B. D DegD D 1116 Lm/m 100 Ŧ 5000 Code Ribbon Plus 82181 D.B.B DORD D ------100 Ŧ 5000 Code Ribbon Plus - LED Strip | topLED 48 W DC 24 V | 9.6 W/m | 82182 D.B.B DORD D 1260 Lm/m 100 -X 1 Code 5000 82194 Ribbon Plus - LED Strip | topLED 72 W DC 24 V | 14.4 W/m | 2022 Lm/m -------50 × \_\_\_\_\_1 Code 82193 **Ribbon Plus** -------50 ×

Systeme - Lineare Elemente | Modular 65013

Systeme - Lineare Elemente | Modular 65013

Components 5000 Code C00418WHDDI Ribbon Plus Dynamic White 100 -Code 5000 2 Ribbon Plus RGBW - LED Strip | topLED 96 W DC 24 V | 19.2 C00417WHVDI W/m 100 aive 5000 Code Ribbon Basic\_V2 - LED Strip | topLED 24 W DC 24 V | 4.8 W/m C00495WH 1 111 111 111 | 522.4 Lm/m 100 × Code 5000 · 1.6 C00496WH Ribbon Basic\_V2 3 313 343 548 618 618 546 61 200 50 × 5000 Code Ribbon HF\_V2 168 LEDs/m - LED Strip | topLED 72 W DC 24 V C00503WH divide are divide a coldivit 200 | 14.4 W/m | 1730 Lm/m 42 Code \_\_\_\_\_\_\_ 5000 \_\_\_\_\_\_ 1.6 Ribbon HF\_V2 238 LEDs/m - LED Strip | topLED 98 W DC 24 V C00504WH n de sen de sen de sen de sen de se | 19.6 W/m | 2350 Lm/m -(mmmmmmmmmmmmm) [mmmmmm] 10 29 × Code 5000 - han 1.6 C00506WH Ribbon HE 160 LEDs/m - LED Strip | topLED 60 W DC 24 V | 200 12 W/m | 1467.8 Lm/m 50 × 5000 Code C00507WH Ribbon HE 160 LEDs/m - LED Strip | topLED 108 W DC 24 V | 200 21.6 W/m | 3037.4 Lm/m

Systeme - Lineare Elemente | Modular 65013

Components			
	5000 1.4 200 	Ribbon HD 160 LEDs/m - LED Strip   topLED 60 W DC 24 V   12 W/m   1434.8 Lm/m	Code C00509WH
	5000 200 	Ribbon HD 160 LEDs/m - LED Strip   topLED 108 W DC 24 V   21.6 W/m   2528.6 Lm/m	Code C00510WH
<mark>: : : :약</mark> : : <b>:</b> : : : : : : : : : : : : : : : : :	5000 200 ← (3 = 1 = 1 = 1 = 1) 50 × 5	Ribbon Slim_V2 120 LEDs/m - LED Strip   topLED 48 W DC 24 V   9.6 W/m   805.8 Lm/m	Code C00511WH
	5000 200 ←⊂s====================================	Ribbon Slim_V2 160 LEDs/m - LED Strip   topLED 52.5 W DC 24 V   10.5 W/m   1326.4 Lm/m	Code C00512WH
	20000 1.6 200 	Ribbon Distance 130 LEDs/m - LED Strip   topLED 192 W DC 48 V   9.6 W/m   1082.35 Lm/m	Code C00514WH
	15000 200 	Ribbon Distance 130 LEDs/m - LED Strip   topLED 207 W DC 48 V   13.8 W/m   1542.13 Lm/m	Code C00515WH

#### Fylo+ Recessed\_5 | Lines | Accessories 65013

