

Uplights | 1 x powerLED 8 W DC 630 mA | CRI 80
80549W06


Single emission uplights for outdoor application. The warm white LED light source with a ultra spot light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 945 lm, with a 118.1 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered. The ingress protection degree is IP68; the total weight is of 0.700 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 98121 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.08 0.08	E(0°) 42131 E(C90) 4.5° 21069 E(C0) 4.6° 21415
1.0	0.16 0.16	E(0°) 10533 E(C90) 4.5° 5267 E(C0) 4.6° 5354
1.5	0.24 0.24	E(0°) 4681 E(C90) 4.5° 2341 E(C0) 4.6° 2379
2.0	0.31 0.32	E(0°) 2633 E(C90) 4.5° 1317 E(C0) 4.6° 1338
2.5	0.39 0.40	E(0°) 1685 E(C90) 4.5° 843 E(C0) 4.6° 857
3.0	0.47 0.48	E(0°) 1170 E(C90) 4.5° 585 E(C0) 4.6° 595

— C0/C180 (Half-peak divergence: 9.2°)
 — C90/C270 (Half-peak divergence: 9.0°)

Energieeffizienzklasse

ieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.

Illuminotechnical Eigenschaften

Light Output Ratio (LOR)	49 %
Lichtstrom (Lichtquelle)	945 lm
Leuchten Lichtstrom	470 lm
Consumption	8 W
Leuchten Lichtausbeute	58 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio

L70 B10 C0 247450h (at Tj 60 Ta 25)

UGR

UGR axial	10.4
UGR transversal	10.2
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Optik C0/C180	9°
Light distribution simmetry	Symmetrical



Suelo_RX | Uplights | Accessories
80549W06



Einbaugehäuse

installationsposition: boden; typ installation: mauerwerk L=110mm, H=155mm, D=110mm.

Material:Kunststoff ABS, farbe:Schwarz.

Code

98121