






Uplights | 220-240 V | 1xGU10
52901



Technical data	
Type	Frame
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x GU10 Max 35W
Optics	Diffused
Safety class	1
IP	IP67
IK	IK09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	Swivelling
total angle (vertical plane)	40 °
Tilting	No
Walk-over	No
Drive-over	3000 Kg
Cable included	No
Resin potting	No
Net weight	0.672 Kg

Finishing casing	
Material	Aluminium
Colour	black
Processing	Coating
Finishing diffuser	
Material	Glass
Colour	transparent
Finishing mounting frame	
Material	Stainless steel 316
Processing	Shot peening



Uplights | 220-240 V | 1xGU10
52901

Single emission uplights for outdoor application. Compatibility:, halogen
35 W; lamp cap 1xGU10.

The device body is made of aluminium and features a black finish, processed by means of coating; the diffuser is made of glass; the mounting frame is made of stainless steel, processed by means of shot peening. The ingress protection degree is IP67; the total weight is of 0.672 kg.

The device features protection class I and can be floor-mounted with an outer casing, code 52700(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Standard Operating Ambient Temperature	-20 / +50°C
--	-------------



	Cable gland	Code <u>84894</u>	
	Cable gland - Terminal with IP68 cable glands for joints and connections.	Code <u>E41017</u>	
		Outer casing Type of installation: masonry L=122mm, H=180mm, D=122mm	Code <u>52700</u>
	Junction - Kit Watertight junction with resin	Code <u>E41025</u>	
	Connector - 3-way connector - IP68 Min.3x0.5mmq / Max 3x1.5mm2	Code <u>84893</u>	