





Projectors | arrayLED 0 W DC - 16 W AC | CRI 80  
64523W07




Technical data	
Type	Surface - -
Installation position	Wall lights - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Asymmetric Wallwasher
Light emission direction	frontal
Nominal power	0 W DC
Total Power	16 W
Nominal input voltage	220 - 240 V AC
Input voltage range	100 - 264 V AC
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP65
IK	IK09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	Swivelling
total angle (vertical plane)	180 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	Yes
Type of light emission	Single emission
Net weight	2 Kg
Electrostatic discharge protection	Yes
Surge protection	0.5 KV
Product technological characteristics	Acquastop - TCS

Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	grey RAL 7021
Processing	Open pore anodizing + Powder Coating
Finishing diffuser	
Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening




Vuelta\_Y | Accessories  
64523W07




Picket  
installation position: land, Cover material: pc

**Code**  
14931



Bracket  
installation position: wall lights L=117mm, H=40mm, D=80mm.  
Material: AISI 304 steel, colour: grey RAL 7021, processing: Powder coating.

**Code**  
64539



Bracket  
L=117mm, H=40mm, D=68,5mm.  
Material: Aluminium 6026, colour: grey RAL 7021, processing: Open pore anodizing + Powder Coating.

**Code**  
64533



Pole

**Code**  
64537