



Ceiling Downlights | arrayLED 0 W DC - 9 W AC  
CRI 90  
**76086W50**



Technical data	
Type	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Wide Flood
Light emission direction	downward
Nominal power	0 W DC
Total Power	9 W
Nominal input voltage	220 - 240 V AC
Input voltage range	176 - 264 V AC
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP40
Optical compartment IP	IP65
IK	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.55 Kg
Electrostatic discharge protection	Yes
Surge protection	0.5 KV
Optics technology	Set-back low glare optics

Finishing casing	
Material	Aluminium 6060 - Aluminium 6060
Colour	Black - 5G 9005 Black
Processing	Powder coating - Powder coating
Finishing diffuser	
Material	Extra clear glass
Colour	transparent