

Wall Lights | arrayLED 0 W DC - 11 W AC | CRI 80 76321N07



05 Down Cell: Elliptic 88 15/30/60 Asym.Ww 07		
Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Asymmetric Wallwasher	
Light emission direction	downward	
Nominal power	0 W DC	
Total Power	11 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	198 - 264 V AC	
CCT / Tone	4000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
IK	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	1.47 Kg	
Electrostatic discharge protection	Yes	
Surge protection	1 KV	



EAE CE 🕱 🕐 🗄 🖂 1668 📭 🖂

Finishing casing	g		
Material	aterial Die-cast Aluminium EN AB - 46100		
Colour	White		
Processing	Open pore anodizing + Powder Coating		
Finishing diffus	er		
Material	Extra clear glass - Tempered		

transparent Silk-screening

Colour

Processing