





Wall Lights | 198-264 V  
1 arrayLED 9.3 W DC - 11 W AC | CRI 80  
**76321N15**



| Technical data                                 |                 |
|--|-----------------|
| Type   | Surface         |
| Installation position                          | Wall lights     |
| Installation environment                       | Outdoor         |
| Light Source                                   | LED             |
| Circuit structure                              | arrayLED        |
| Optics   | Spot            |
| Light emission direction                       | downward        |
| Nominal power                                  | 9.3 W DC        |
| Total Power                                    | 11 W            |
| Source lumens                                  | 1354 lm         |
| Nominal input voltage                          | 220 - 240 V AC  |
| Input voltage range                            | 198 - 264 V AC  |
| Frequency                                      | 50 - 60 Hz      |
| CCT / Tone                                     | 4000 K          |
| Colour rendering index                         | 80 Ra           |
| C.C. / C.V.                                    | AC              |
| Safety class                                   | 1               |
| IP   | IP65            |
| IK   | IK08            |
| Glow wire test                                 | 850°            |
| Direct mounting on normally flammable surfaces | Yes             |
| CE   | Yes             |
| Driver included                                | Driver          |
| Dimmable article                               | No              |
| Directional                                    | No              |
| Tilting  | No              |
| Walk-over                                      | No              |
| Drive-over                                     | No              |
| Cable included                                 | No              |
| Resin potting                                  | No              |
| Type of light emission                         | Single emission |
| Net weight                                     | 1.47 Kg         |
| Electrostatic discharge protection             | Yes             |
| Surge protection                               | 1 KV            |

| Finishing casing   |                                      |
|--------------------|--------------------------------------|
| Material           | Die-cast Aluminium EN AB - 46100     |
| Colour             | White                                |
| Processing         | Open pore anodizing + Powder Coating |
| Finishing diffuser |                                      |
| Material           | Extra clear glass - Tempered         |
| Colour             | transparent                          |
| Processing         | Silk-screening                       |



Wall Lights | 198-264 V | 1 arrayLED 9.3 W DC - 11 W AC | CRI 80 | Base  
76321N15

Single emission wall lights for outdoor application. The natural white LED light source with a spot light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1354 lm, with a 145.6 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a white finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP65; the total weight is of 1.47 kg.

The total absorbed power is 11 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class E.

### Illuminotechnical Features

|                                       |                |
|---------------------------------------|----------------|
| Light Output Ratio (LOR)              | 67 %           |
| Source lumens                         | 1354 lm        |
| Delivered lumens                      | 915 lm         |
| Consumption                           | 11 W           |
| Luminaire efficacy                    | 83 lm/W        |
| Colour temperature                    | 4000 K         |
| Standard Deviation of Colour Matching | 2 Step MacAdam |
| Colour rendering index                | 80 Ra          |

|  |             |
|--|-------------|
| Standard Operating Ambient Temperature | -20 / +50°C |
| Ordinary temperature on the glass      | 40°C        |

### LED Life / Failure Ratio

L70 B10 C0 252000h (at Tj 65 Ta 25 )

### UGR

|                   |          |
|-------------------|----------|
| UGR axial         | 13.5     |
| UGR transversal   | 15.2     |
| X=4H   Y=8H       | S=0.25H  |
| Reflection factor | 70/50/20 |

### OPTICAL

|                             |             |
|-----------------------------|-------------|
| C0/C180 optics              | 15°         |
| Light distribution simmetry | Symmetrical |

