



Wall Lights | 198-264 V  
1 arrayLED 9.3 W DC - 11 W AC | CRI 80

**76323N60**



## Technical data

Type	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Wide Flood
Light emission direction	downward
Nominal power	9.3 W DC
Total Power	11 W
Source lumens	1354 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.47 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV

## Finishing casing

Material	Die-cast Aluminium EN AB - 46100
Colour	Grey
Processing	Open pore anodizing + Powder Coating

## Finishing diffuser

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening

Wall Lights | 198-264 V | 1 arrayLED 9.3 W DC - 11 W AC | CRI 80 | Base  
**76323N60**

Single emission wall lights for outdoor application. The natural white LED light source with a wide flood light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1354 lm, with a 145.6 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a grey finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP65; the total weight is of 1.47 kg.

The total absorbed power is 11 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class E.

### Illuminotechnical Features

Light Output Ratio (LOR)	71 %
Source lumens	1354 lm
Delivered lumens	963 lm
Consumption	11 W
Luminaire efficacy	87 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra

Standard Operating Ambient Temperature -20 / +50°C

Ordinary temperature on the glass 40°C

### LED Life / Failure Ratio

L70 B10 C0 252000h (at Tj 65 Ta 25 )

### UGR

UGR axial 17.4

UGR transversal 17.9


X=4H | Y=8H S=0.25H

Reflection factor 70/50/20

### OPTICAL

C0/C180 optics 51°

Light distribution simmetry Symmetrical



Distance [m]	Cone diameter [m]	Intensity [lx]
0.5	0.47 0.48	E(0°) 5671 E(C90) 2118 E(C0) 2100
1.0	0.95 0.96	E(0°) 1418 E(C90) 530 E(C0) 525
1.5	1.42 1.44	E(0°) 630 E(C90) 235 E(C0) 233
2.0	1.89 1.92	E(0°) 354 E(C90) 132 E(C0) 131
2.5	2.36 2.40	E(0°) 227 E(C90) 85 E(C0) 84
3.0	2.84 2.87	E(0°) 158 E(C90) 59 E(C0) 58

Distance [m] Cone diameter [m] Illuminance [lx]

— C0/C180 (Half-peak divergence: 51.2°)  
 — C90/C270 (Half-peak divergence: 50.6°)