## Cubit Pro

## Wall Lights | x powerLEDs 0 W DC - 11 W AC CRI 80

101

76324M05

CE

Driver included

Dimmable article

Directional

Walk-over

Drive-over

Cable included

Type of light emission

Electrostatic discharge protection

Resin potting

Net weight

Surge protection

Tilting



	05	Down Cell: 15/30/60	Elliptic <b>88</b> Asym.Ww <b>07</b>		
Technical da	ta				
Туре				Surface	
Installation po	sition			Wall lights	
Installation en	vironment			Outdoor	
Light Source L				LED	
Circuit structure powe				powerLEDs	
Optics	Ultra Spot				
Light emission direction downwar					
Nominal power 0 W DC				0 W DC	
Total Power 11 W				11 W	
Nominal input voltage				220 - 240 V AC	
Input voltage range 198				198 - 264 V AC	
CCT / Tone 2700 K				2700 K	
Colour rendering index 80 Ra				80 Ra	
C.C. / C.V. A0				AC	
Safety class				1	
IP				IP65	
IK		IK08			
Glow wire test 850°					
Direct mounting on normally flammable surfaces Yes					

Yes

No

No

No

No

No

No


No

Yes


1 KV

Single emission 1.47 Kg

Driver



EAC	CE	$\overline{\mathbb{X}}$	$\odot$	Ŧ	IK08	IP65	I	



Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening