
Wall Lights | arrayLED 0 W DC - 7.5 W AC | CRI 80 76327M60





Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Wide Flood	
Light emission direction	downward	
Nominal power	0 W DC	
Total Power	7.5 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	198 - 264 V AC	
CCT / Tone	2700 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
К	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	DALI-2	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	1.47 Kg	
Electrostatic discharge protection	Yes	
Surge protection	1 KV	



EIII - CE 🕱 🕐 🗄 - IKO8 11965 🗉 🦳

Finishing casing	9	
Material	Die-cast Aluminium EN AB - 46100	
Colour	Black	
Processing	Open pore anodizing + Powder Coating	
Finishing diffus	er	
Motorial	Extra clear clean Tompored	

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening