

Wall Lights | arrayLED 0 W AC 200-264 V AC CRI 80





Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Double Extra Wide Flood	
Light emission direction	downward and upward	
Nominal power	0 W AC	
Input voltage range	200-264V	
CCT / Tone	3000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
IK	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Double emission	
Net weight	1.5 Kg	
Electrostatic discharge protection	No	
Surge protection	1.5 KV	
















Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating
Finishing diffuser	
NA-4i-I	Citar along plans. Transport

i misimig umuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	