
Cubit

Wall Lights | arrayLED 0 W AC 200-264 V AC CRI 80 76577N15





Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Spot	
Light emission direction	downward	
Nominal power	0 W AC	
Input voltage range	200-264V	
CCT / Tone	4000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
IK	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	1.44 Kg	
Electrostatic discharge protection	No	
Surge protection	1.5 KV	



Eff. CE 🕱 🕐 🗄 IKO8 1P65 🗉 🏹

11	
	113
[[

Finishing casing	9	
Material	Die-cast Aluminium EN AB - 46100	
Colour	Dark brown	
Processing	Open pore anodizing + Powder Coating	
Finishing diffus	er	
Material	Extra clear glass - Tempered	
Colour	transparent	

Silk-screening

_. . . .

Processing