Cubit Pro



Wall Lights | arrayLED 0 W DC - 8.7 W AC | CRI 80 **76586M60**








| 13/30/00 Asynt.vv 07 | |
|--|----------------------|
| Technical data | |
| Туре | Surface |
| Installation position | Wall lights |
| Installation environment | Outdoor |
| Light Source | LED |
| Circuit structure | arrayLED |
| Optics | Medium Wide Flood |
| Light emission direction | downward |
| Nominal power | 0 W DC |
| Total Power | 8.7 W |
| Nominal input voltage | 220 - 240 V AC |
| Input voltage range | 180 - 264 V AC |
| CCT / Tone | 2700 K |
| Colour rendering index | 80 Ra |
| C.C. / C.V. | AC |
| Safety class | 1 |
| IP | IP65 |
| IK | IK08 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | Driver |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Single emission |
| Net weight | 0.77 Kg |
| Electrostatic discharge protection | Yes |
| Surge protection | 1 KV |
| | |





| Finishing casing | | |
|------------------|--------------------------------------|--|
| Material | Die-cast Aluminium EN AB - 46100 | |
| Colour | Grey | |
| Processing | Open pore anodizing + Powder Coating | |

| Finishing diffuser | | |
|--------------------|------------------------------|--|
| Material | Extra clear glass - Tempered | |
| Colour | transparent | |
| Processing | Silk-screening | |