
## Cubit Pro

## Wall Lights x powerLEDs - arrayLED 0 W DC 630 mA | CRI 80 76629M15



Down Cell:	Un:

Technical data	
	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs + arrayLED
Optics	Ultra Spot + Spot
Light emission direction	upward + downward
Nominal power	0 W DC
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	0.8 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV



[Ħ < € 🕱 Φ 💿 cc. 🖂 K08 P65 F 🗋

	89
88	°

Finishing casing	]
Material	Die-cast Aluminium EN AB - 46100
Colour	White
Processing	Open pore anodizing + Powder Coating
Finishing diffuse	er
Material	Extra clear glass - Tempered

transparent

Silk-screening

Colour

Processing

1/1	5.02.2025
1/1	J.02.202J