





Wall Lights | 198-264 V AC /220-240 V DC | 3 x powerLED 6.3 W DC - 7 W AC | CRI 80 |  
 Base  
**76923N15**

Single emission wall lights for outdoor application. The natural white LED light source with a spot light distribution is composed of 3 powerLEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 909 lm, with a 144.3 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a white finish, processed by means of powder coating; the diffuser is made of extra clear glass with a silk-screening treatment; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP65; the total weight is of 1.181 kg.

The total absorbed power is 7 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class D.

### Illuminotechnical Features

|                                       |          |
|---------------------------------------|----------|
| Light Output Ratio (LOR)              | 58 %     |
| Source lumens                         | 909 lm   |
| Delivered lumens                      | 529 lm   |
| Consumption                           | 7 W      |
| Luminaire efficacy                    | 75 lm/W  |
| Colour temperature                    | 4000 K   |
| Standard Deviation of Colour Matching | 1.5 Step |
| Colour rendering index                | 80 Ra    |

|  |             |
|--|-------------|
| Standard Operating Ambient Temperature | -20 / +50°C |
| Ordinary temperature on the glass      | 40°C        |

### LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25 )

### OPTICAL

|                             |              |
|-----------------------------|--------------|
| C0/C180 optics              | 21°          |
| Light distribution symmetry | Asymmetrical |

