## Skin\_WF


## Wall Lights | x powerLED 0 W DC - 7 W AC | CRI 80 76924W30





| Technical data                                 |                      |
|--|----------------------|
| Туре   | Surface              |
| Installation position                          | Wall lights          |
| Installation environment                       | Outdoor              |
| Light Source                                   | LED                  |
| Circuit structure                              | powerLED             |
| Optics   | Medium Wide<br>Flood |
| Light emission direction                       | downward             |
| Nominal power                                  | 0 W DC               |
| Total Power                                    | 7 W                  |
| Nominal input voltage                          | 220 - 240 V AC       |
| Input voltage range                            | 198 - 264 V AC       |
| CCT / Tone                                     | 3000 K               |
| Colour rendering index                         | 80 Ra                |
| C.C. / C.V.                                    | AC                   |
| Safety class                                   | 1                    |
| IP   | IP65                 |
| IK   | IK06                 |
| Glow wire test                                 | 850°                 |
| Direct mounting on normally flammable surfaces | No                   |
| CE   | Yes                  |
| Driver included                                | Driver               |
| Dimmable article                               | DALI-2 - PUSH<br>DIM |
| Directional                                    | No                   |
| Tilting  | No                   |
| Walk-over                                      | No                   |
| Drive-over                                     | No                   |
| Cable included                                 | No                   |
| Resin potting                                  | No                   |
| Type of light emission                         | Single emission      |
| Net weight                                     | 1.181 Kg             |
| Electrostatic discharge protection             | Yes                  |
| Surge protection                               | 1 KV                 |

## [f][ 🚾 < 🕱 🕐 🛓 🖻 K06 P65 🗉 🏹



| Finishing casin  | g  |
|------------------|--|
| Material         | Die-cast Aluminium EN AB - 46100               |
| Colour           | Black  |
| Processing       | Powder coating                                 |
|                  |  |
| Finishing diffus | ser  |
| Material         | UV Resistant Polycarbonate - Extra clear glass |
| Colour           | black - transparent                            |
| Processing       | Silk-screening                                 |
|                  |  |
| Finishing brack  | et   |
| Material         | AISI 304 steel                                 |
| Colour           | steel  |
|                  |  |