

Wall Lights | x powerLEDs 0 W DC - 21 W AC CRI 80

77019N07





Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Double Asymmetric
Light emission direction	downward and upward
Nominal power	0 W DC
Total Power	21 W
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK06
Glow wire test	850°
Direct mounting on normally flammable surfaces	No
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	1.646 Kg
Electrostatic discharge protection	Yes
Surge protection	2 KV
















Finishing casin	g	
Material	Die-cast Aluminium EN AB - 46100	
Colour	Black	
Processing	Powder coating	
Finishing diffus	er	
Material	UV Resistant Polycarbonate - Extra clear glass	

Processing	Silk-screening	
Finishing brack	et	
Material	AISI 304 steel	
Colour	steel	

black - transparent

Colour