

#### Projectors | 176-264 V | 1 arrayLED 16 W DC - 18 W AC | CRI 90 77052W15




















| Technical data                                 | T .             |
|--|-----------------|
| Type   | Track           |
| Installation position                          | Ceiling         |
| Installation environment                       | Indoor          |
| Light Source                                   | LED             |
| Circuit structure                              | arrayLED        |
| Optics   | Spot            |
| Light emission direction                       | frontal         |
| Nominal power                                  | 16 W DC         |
| Total Power                                    | 18 W            |
| Source lumens                                  | 2572 lm         |
| Nominal input voltage                          | 220 - 240 V AC  |
| Input voltage range                            | 176 - 264 V AC  |
| Frequency                                      | 50 - 60 Hz      |
| CCT / Tone                                     | 3000 K          |
| Colour rendering index                         | 90 Ra           |
| C.C. / C.V.                                    | AC              |
| Safety class                                   | 2               |
| IP   | IP20            |
| Glow wire test                                 | 850°            |
| Direct mounting on normally flammable surfaces | Yes             |
| CE   | Yes             |
| Driver included                                | Driver          |
| Dimmable article                               | No              |
| Directional                                    | Swivelling      |
| total angle (vertical plane)                   | 90 °            |
| total angle (horizontal plane)                 | 360 °           |
| Tilting  | No              |
| Walk-over                                      | No              |
| Drive-over                                     | No              |
| Cable included                                 | No              |
| Resin potting                                  | No              |
| Type of light emission                         | Single emission |
| Net weight                                     | 0.412 Kg        |
| Electrostatic discharge protection             | Yes             |
| Surge protection                               | 2 KV            |
|  |                 |

| Finishing casin | g                                |
|-----------------|----------------------------------|
| Material        | Die-cast Aluminium EN AB - 46100 |
| Colour          | White                            |
| Processing      | Powder coating                   |



#### Projectors | 176-264 V | 1 array LED 16 W DC - 18 W AC | CRI 90 | Base $\bf 77052W15$


Single emission projectors for indoor application. The warm white LED light source with a spot light distribution is composed of 1 arrayled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2572 lm, with a 160.8 lm/W nominal luminous efficacy.


The device body is made of die-cast aluminium en ab - 46100 and features a white finish, processed by means of powder coating. The ingress protection degree is IP20; the total weight is of 0.412 kg.

The total absorbed power is 18 W.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





#### Energy efficiency class

This product contains a light source of energy efficiency class E.

| Illuminotechnical Features             |                |
|--|----------------|
| Light Output Ratio (LOR)               | 68 %           |
| Source lumens                          | 2572 lm        |
| Delivered lumens                       | 1769 lm        |
| Consumption                            | 18 W           |
| Luminaire efficacy                     | 98 lm/W        |
| Colour temperature                     | 3000 K         |
| Standard Deviation of Colour Matching  | 2 Step MacAdam |
| Colour rendering index                 | 90 Ra          |
| Colour Rendering Index                 | 60 R9          |
| Black Body Locus                       | On             |
|  |                |
| Standard Operating Ambient Temperature | -20 / +50°C    |
| Ordinary temperature on the glass      | 40°C           |


#### LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25)

| UGR               |          |
|-------------------|----------|
| UGR axial         | 18       |
| UGR transversal   | 18       |
| X=4H   Y=8H       | S=0.25H  |
| Reflection factor | 70/50/20 |

| OPTICAL                     |             |
|-----------------------------|-------------|
| C0/C180 optics              | 18°         |
| Light distribution simmetry | Symmetrical |

#### COLOR VECTOR GRAPHIC







### Optus\_T | Projectors | Accessories **77052W15**

| and the second   | 95<br>8 31 148 | Power supply - White Right power supply header (9001/W) Material:PC, colour:white. | <b>Code</b><br>81033 |
|--|----------------|--|----------------------|
| a section of the sect | 95<br>9 31 148 | Power supply - White left power supply header (9002/W) Material:PC, colour:white.  | <b>Code</b><br>81036 |
|  | 95<br>31 148   | Power supply - Black left power supply header (9002/B) Material:PC, colour:black.  | <b>Code</b><br>81037 |
|  | 95<br>8 31 148 | Power supply - Black Right power supply header (9001/B) Material:PC, colour:black. | <b>Code</b><br>81034 |
| STÜCCHI  |                | Closing cap - White end cap 9004/W<br>Material:PC, colour:white.                   | <b>Code</b><br>80999 |
|  |                | Closing cap - Black end cap 9004/B<br>Material:PC, colour:black.                   | <b>Code</b><br>81000 |
| STUCCHI  |                | Closing cap - Recessed white end cap 9004-R/W Material:PC, colour:white.           | <b>Code</b><br>81002 |
|  | 8 EVECH        | Closing cap - Recessed black end cap 9004-R/B Material:PC, colour:black.           | <b>Code</b><br>81003 |

Material:PC, colour:black.



### Optus\_T | Projectors | Accessories **77052W15**

|     | 3 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5         | Closing cap - White gasket (S-9001/115-W)<br>Material:white.   |                     | <b>Code</b><br>81084 |
|-----|---|--|---------------------|----------------------|
|     | 9.85  | Closing cap - Black gasket (S-9001/115-B) Material:black, colour:black.  |                     | <b>Code</b><br>81085 |
| *** |   | Ceiling rose - 1.5m white pendant luminaires kit + bracket (9000-KIT5-1,5-W) Material:plastic, colour:white.   |                     | <b>Code</b><br>81012 |
| *   | Ø. 32   | Ceiling rose - 1.5m black pendant luminaires kit + bracket ((9000-KIT5-1,5-B) Material:plastic, colour:black.  |                     | <b>Code</b><br>81014 |
|     | 92.332<br>1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | Ceiling rose - 5m white pendant luminaires kit + bracket (9000-KIT5-5-W) Material:plastic, colour:white.       |                     | <b>Code</b><br>81013 |
| *   |   | Ceiling rose - 5m black pendant luminaires kit + bracket (9000-KIT5-5-B) Material:plastic, colour:black.       |                     | <b>Code</b><br>81015 |
|     | 2 1 1 40  | Bracket - Anodized fixing bracket (S-9000/131) L=35mm, H=14mm, D=24mm. Material:Aluminium, colour:translucent. | Finish<br>Anod. Al. | <b>Code</b><br>81086 |
|     | 24 180 R  | Bracket - Anodized stiffening bracket (S-9000/333) L=180mm, H=24mm, D=26mm.                                    | Finish              | <b>Code</b> 81024    |

 ${\it Material:} A luminium, \ colour: Anodised \ A luminum, \ processing: Anodisation.$ 



### Optus\_T | Projectors | Accessories **77052W15**





Bracket - White stiffening bracket (S-9000/333-W)
L=180mm, H=24mm, D=20mm.

Material: Aluminium, colour: white RAL 9010, processing: Coating.

Finish White Code

81025





Bracket - Black stiffening bracket (S-9000/333-B) L=180mm, H=24mm, D=20mm.

Material: Aluminium, colour: black RAL 9005, processing: Coating.

Finish Black Code

81026





Bracket - White fixing braket (S-9000/131-W) L=35mm, H=14mm, D=24mm.

Material:Aluminium, colour:white, processing:Coating.

Finish White Code

81087





Bracket - Black fixing braket (S-9000/131-B)
L=35mm, H=14mm, D=24mm.
Material:Aluminium, colour:Black, processing:Coating.

Finish

Code

81088





Junction - White electrical junction - internal (9003/W)
Type linear.
Material:PC, colour:white.

Finish White Code

81039





Junction - Black electrical junction - internal (9003/B) Type linear.

Material:PC, colour:black.

Finish

Code

81040






Junction - White power supply junction - central (9010/W) Type linear.

Material:PC, colour:white.

Finish White Code

81042





Junction - White L junction - internal (9011/W)

Type linear.

Material:PC, colour:white.


Finish White Code

81045



#### Optus\_T | Projectors | Accessories 77052W15





Junction - White L junction - external (9012/W)

Type linear.

Material:PC, colour:white.

Finish White

Code

81048





Junction - Flexible white junction (9018/W)

Type flexible curve.

Material:PC, colour:white.

Finish White

Code 81066





Junction - White X junction (9017/W)

Type linear.


Material:PC, colour:white.

Finish

Code

White 81063





Junction - Left white T junction - external (9013/W)

Type linear.


Material:PC, colour:white.

**Finish** White

Code

81051





Junction - Right white T junction - external (9014/W)

Type linear.


Material:PC, colour:white.

Finish White

Code

81054





Junction - Left white T junction - internal (9015/W)


Type linear.

Material:PC, colour:white.

**Finish** White

Code 81057





Junction - Right White T junction - internal (9016/W)

Type linear.

Material:PC, colour:white.

Finish White

Code 81060



Junction - Black power supply junction - centrale (9010/B)

Type linear.

Material:PC, colour:black.

**Finish** 

Code

81043



### Optus\_T | Projectors | Accessories **77052W15**





Junction - Black L junction - internal (9011/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81046





Junction - Black L junction - external (9012/B)

Type linear.

Material:PC, colour:black.

Finish Black Code

81049





Junction - Flexible black junction (9018/B)

Type flexible curve.

Material:PC, colour:black.

Finish

Code

81067





Junction - Black X junction (9017/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81064





Junction - Black left T junction - external (9013/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81052





Junction - Right black T junction - external (9014/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81055





Junction - Left black T junction - internal (9015/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81058





Junction - Right black T junction - internal (9016/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81061



|   |  | Suspensions - 1.5m white pendant luminaires kit (9000-KIT3-1,5-W) Material:plastic, colour:white. | <b>Code</b><br>81006 |
|---|--|---|----------------------|
|   |  | Suspensions - 5m white pendant luminaires kit (9000-KIT3-5-W) Material:plastic, colour:white.     | <b>Code</b><br>81007 |
| ÷ | 32<br>\$\display\$ \qquad \qqqq \qqq \qqqq \qqq \qqqq \q | Suspensions - 1.5m black pendant luminaires kit (9000-KIT3-1,5-B) Material:plastic, colour:black. | <b>Code</b><br>81008 |
| † | 32<br>32<br>35<br>32<br>35<br>32<br>35<br>32<br>35<br>32<br>35<br>35<br>35<br>35<br>35<br>35<br>35<br>35<br>35<br>35   | Suspensions - 5m black pendant luminaires kit (9000-KIT3-5-B) Material:plastic, colour:black.     | <b>Code</b><br>81009 |
|   |  | Suspensions - White rigid suspension clip (S-9000-P2-W) Material:plastic, colour:white.           | <b>Code</b><br>81018 |
|   |  | Suspensions - Black rigid suspension clip (S-9000-P2-B)  Material:plastic, colour:black.          | <b>Code</b><br>81019 |
|   |  | Suspensions - White rigid suspension 1m (S-9000-P3-W) Material:plastic, colour:white.             | <b>Code</b><br>81021 |
|   |  | Suspensions - Black rigid suspension 1m (S-9000-P3-B)  Material:plastic, colour:black.            | <b>Code</b><br>81022 |



|          | *************************************** | Cable cover - White recessed cover (S-9001-R/6-W) Material:PC, colour:white.                 | <b>Code</b><br>81069 |
|----------|---|--|----------------------|
|          | ● 6.5.1Σ(m) ο                           | Cable cover - White cover for recessed junction (S-9010-R/6-W)  Material:PC, colour:white.   | <b>Code</b><br>81072 |
| - Arthur | (a.2253.m.)©                            | Cable cover - White cover for recessed L junction (S-9011-R/6-W) Material:PC, colour:white.  | <b>Code</b><br>81075 |
| - 1150   | + (12552) +                             | Cable cover - White cover for recessed T junction (S-9013-R/6-W)  Material:PC, colour:white. | <b>Code</b><br>81078 |
|          | 0 0 0 mHm 0 0 0                         | Cable cover - White cover for recessed X junction (S-9017-R/6-W)  Material:PC, colour:white. | <b>Code</b><br>81081 |
|          | T T T T T T T T T T T T T T T T T T T   | Cable cover - Black recessed cover (S-9001-R/6-B) Material:PC, colour:black.                 | <b>Code</b><br>81070 |
|          |   | Cable cover - Black cover for recessed junction (S-9010-R/6-B)  Material:PC, colour:black.   | <b>Code</b><br>81073 |
|          | O (ATHYANI)O                            | Cable cover Material:PC, colour:black.   | <b>Code</b><br>81076 |



|      | + (c1)Y(x) +  | Cable cover - Black cover for recessed T junction (S-9013-R/6-B)  Material:PC, colour:black. | <b>Code</b><br>81079 |
|------|---|--|----------------------|
|      | 0 (12 May 0)  | Cable cover - Black cover for recessed X junction (S-9017-R/6-B)  Material:PC, colour:black. | <b>Code</b><br>81082 |
|      |   | Cable cover<br>Material:white.   | <b>Code</b><br>83249 |
|      |   | Cable cover<br>Material:black, colour:black.   | <b>Code</b><br>83250 |
| 5.00 | 2 13.5<br>2 10 10 10 10 10 10 10 10 10 10 10 10 10  | White three-phase/DALI adapter (9009/W)  | <b>Code</b><br>81094 |
|      | S 100 | White three-phase adapter (9009-4/W)   | <b>Code</b><br>81091 |
|      |   | Black three-phase/DALI adapter (9009/B)  | <b>Code</b><br>81095 |
|      |   | Black trhee-phase adapter (9009-4/B)   | <b>Code</b><br>81093 |



### Optus\_T | Projectors | Accessories **77052W15**

|  | Tool - Cutter S-9000/T  | <b>Sode</b><br>1005     |
|--|---|-------------------------|
| 31.4<br>(1) (2) (3) (3) (3) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4 | Track - Three-phase Recessed White DALI Track, 1 m (9000-1/W-R) Length: 1000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.  | <br><b>Code</b><br>0990 |
| 31.A<br>(1) (2) (3) (3) (2) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4     | Track - Three-phase Recessed White DALI Track, 2 m (9000-2/W-R) Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.  | <br><b>Sode</b><br>0991 |
| 31.4<br>(1) (2) (2) (3) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4     | Track - Trhee-phase Recessed White DALI Track, 3 m ( 9000-3/W-R) Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating. | <br><b>ode</b><br>0992  |
| 31.4<br>(1) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4             | Track - Three-phase Recessed Grey DALI Track, 1 m (9000-1/B-R) Length: 1000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.   | <b>Ode</b>              |
| 31.4<br>(1) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4             | Track - Three-phase Recessed Black DALI Track, 2 m (9000-1/B-R) Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.  | <b>Gode</b> 0994        |
| 31.4<br>(1) (2) (2) (3) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4     | Track - Three-phase Recessed Black DALI Track, 3 m (9000-3/B-R) Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.  | <b>Ode</b>              |
| 37.8   | Track Length: 1000mm; Type of track: Standard.  | <br>3336                |

 $Material: Aluminium,\ colour: White,\ processing: Coating.$ 



|   | 37.8  | Track Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.                   | Finish Code White 83337 |
|---|-------|--|-------------------------|
|   | 37.8  | Track Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.                   | Finish Code White 83338 |
|   | 37.8  | Track Length: 1000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.                   | Finish Code Black 83339 |
|   | 37.8  | Track Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.                   | Finish Code Black 83340 |
|   | 37.8  | Track Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.                   | Finish Code Black 83341 |
|   | 035.5 | Anti-glare - Accessory for focal kit with code 83347. Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black. | <b>Code</b><br>99841    |
| 0 |       | Anti-glare<br>Anti-glare Type: elliptical filter.<br>Material:Pom-C, colour:Black.                                     | <b>Code</b><br>83345    |
|   |       | Anti-glare Anti-glare Type: cross louvres. Material:Pom-C, colour:Black.   | <b>Code</b><br>83344    |



|         | Anti-glare  | <b>Code</b> 83343 |
|---------|---|-------------------|
|         | Anti-glare Type: 45° cylindrical screen.  Material:Pom-C, colour:Black.   | 63343             |
|         | Material.FonPo, colour.black.   |                   |
|         |   | Code              |
|         | Anti-glare  | 83346             |
|         | Anti-glare Type: honeycomb louvre.  Material:Pom-C, colour:Black.   |                   |
|         |   |                   |
|         | Anti-glare  | Code              |
|         | Anti-glare Type: cylindrical screen.  | 83342             |
|         | Material:Pom-C, colour:Black.   |                   |
|         |   | Code              |
|         | Optics Light distribution: spot,Cover material: uv resistant polycarbonate  | 83348             |
|         | Light distribution. Spot, cover material: av resistant peryodibonate  |                   |
|         |   | Code              |
| All The | Optics  | 83349             |
|         | Light distribution: medium flood,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate                     |                   |
|         |   | Code              |
|         | Optics  | 83347             |
|         | Light distribution: adjustable,Cover material: ,aluminium   |                   |
|         |   | Code              |
|         | Optics Light distribution: flood Cover material: The registent polycorhonate the registent                                  | 83350             |
|         | Light distribution: flood,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate |                   |
|         |   |                   |