## Stadium




## Wall Lights | topLED 0 W DC - 7.8 W AC | CRI 80 77186W00









Technical data		
Туре	Surface	
Installation position	Wall lights - Ceiling	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	topLED	
Optics	Diffused	
Light emission direction	frontal	
Nominal power	0 W DC	
Total Power	7.8 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	198 - 264 V AC	
CCT / Tone	3000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	2	
IP	IP65	
IK	IK10	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.4 Kg	
Electrostatic discharge protection	Yes	
Surge protection	1 KV	


Finishing casing	
Material	UV Resistant Polycarbonate
Colour	Opal white
Finishing diffuser	
Material	UV Resistant Polycarbonate
Colour	opaline

## Stadium



## Stadium | Wall Lights | Accessories **77186W00**






Bracket - Inclined bracket for wall installation installation position: wall lights L=204.6mm, H=24.3mm, D=81mm. Material:Iron, colour:White, processing:Powder coating.

Code

83247





Bracket - Inclined bracket for wall installation installation position: wall lights L=204.6mm, H=24.3mm, D=81mm. Material:Iron, colour:Black, processing:Coating.

Finish

Code

Black 83248