

## Uplights | arrayLED 0 W DC 24 V | CRI 80 77300N60


























Technical data	
Туре	Walk Over
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Medium Wide Flood
Light emission direction	upward
Nominal power	0 W DC
Input voltage range	24 V
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
C.V C.C. Converter	Converter 24V included
Dimmable article	DALI - 1-10V
Directional	No
Tilting	Yes
total angle (vertical plane)	40 °
Walk-over	Yes
Drive-over	2000 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.45 Kg
Electrostatic discharge protection	No
Surge protection	No



Finishing casing		
Material	Die-cast Aluminium EN AB - 46100	
Colour	black	
Processing	Open pore anodizing + Powder Coating	

Finishing diffuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	

Finishing flange		
Material	AISI 316 steel	
Colour	steel	
Processing	Brushing	

Cables Electrification		
Cable connector	No	

Honey comb

Acquastop - TVS


Optics technology

Product technological characteristics

## Orma\_QJ



Orma\_QJ | Uplights | Accessories **77300N60** 



Outer casing installation position: floor, land; type of installation: masonry L=97mm, H=93mm, D=97mm. Material:ABS Plastic, colour:black.

Code

83411