



Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90  
77330M30



64

Technical data	
Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Medium Flood
Light emission direction	downward
Nominal power	9 W DC
Source lumens	1059 lm
Input voltage range	700mA
CCT / Tone	2700 K
Colour rendering index	90 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP40
Optical compartment IP	IP65
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.2 Kg
Electrostatic discharge protection	No
Surge protection	No

### Finishing casing

Material	Technopolymer
Colour	White RAL 9003

### Finishing diffuser

Material	UV Resistant Polycarbonate
Colour	transparent

### Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Colour	Aluminium
Processing	Polishing

### Electronics

	99147 On/Off Driver 198~264V AC (1 - 2 art.)
	99735 Multi Power 198~264V AC / 180~275V DC (1 art.)
	99733 1-10V Multi Power 198~264V AC / 180~275V DC (1 art.)
	C-E100012 Push and Simply Dim - DALI-2 Controller (1 art.)
	C-E100016 Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



## Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90 | Base 77330M30

Single emission recessed downlights for indoor application. The super warm white LED light source with a medium flood light distribution is composed of 1 arrayed LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 1059 lm, with a 117.7 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white ral 9003 finish; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP40; the total weight is of 0.2 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 9 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be ceiling-mounted, with a 64 mm diameter hole (in plasterboard) with an outer casing, code 99849(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class F.

### Illuminotechnical Features

Light Output Ratio (LOR)	62 %
Source lumens	1059 lm
Delivered lumens	664 lm
Consumption	9 W
Luminaire efficacy	73 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	90 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio


L70 B10 C0 112960h (at Tj 65 Ta 25 )

### UGR

UGR axial	9.8
UGR transversal	9.8
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	30°
Light distribution simmetry	Symmetrical



Distance [m]	Cone diameter [m]	illuminance [lx]	E(0°)	E(C90)	E(C0)
0.5	0.26 0.27	8810 4004 3988	14.8°	14.8°	15.2°
1.0	0.53 0.54	2202 1001 997	14.8°	14.8°	15.2°
1.5	0.79 0.82	979 445 443	14.8°	14.8°	15.2°
2.0	1.06 1.09	551 250 249	14.8°	14.8°	15.2°
2.5	1.32 1.36	352 160 160	14.8°	14.8°	15.2°
3.0	1.59 1.63	245 111 111	14.8°	14.8°	15.2°









Distance [m]      Cone diameter [m]      illuminance [lx]


— C0/C180 (Half-peak divergence: 30.4°)  
— C90/C270 (Half-peak divergence: 29.6°)



		<p>Outer casing                      installation position: ceiling; type of installation: masonry L=200mm, H=113mm, D=137mm.                      Material:polypropylene, colour:white.</p>	<p><b>Code</b>  <u>89373</u></p>
		<p>Outer casing                      installation position: ceiling; type of installation: masonry L=370mm, H=120mm, D=200mm.                      Material:polypropylene, colour:white.</p>	<p><b>Code</b>  <u>89374</u></p>
		<p>Outer casing                      installation position: ceiling; type of installation: drywall L=77.5mm, H=28mm, D=77.5mm.                      Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.</p>	<p><b>Finish</b>  <span style="background-color: #cccccc; display: inline-block; width: 20px; height: 10px;"></span> <b>Code</b>  <u>99849</u></p>
		<p>Optics                      Light distribution: medium wide flood,Cover material: uv resistant polycarbonate</p>	<p><b>Code</b>  <u>83372</u></p>
		<p>Optics                      Light distribution: medium flood,Cover material: uv resistant polycarbonate</p>	<p><b>Code</b>  <u>83371</u></p>
		<p>Optics                      Light distribution: spot,Cover material: uv resistant polycarbonate</p>	<p><b>Code</b>  <u>83370</u></p>
		<p>Anti-glare                      Anti-glare Type: honeycomb louvre.                      Material:Pom-C, colour:Black.</p>	<p><b>Code</b>  <u>83367</u></p>
		<p>Diffuser                      Diffuser Type: elliptical filter</p>	<p><b>Code</b>  <u>83368</u></p>



	<p>Diffuser                  Diffuser Type: aesthetic filter</p>	<p><b>Code</b>  <u>83369</u></p>
	<p>White Quantum_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83361</u></p>
	<p>Black Quantum_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83362</u></p>
	<p>Black Vos_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83366</u></p>
	<p>White Vos_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83365</u></p>
	<p>Black Warp_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83364</u></p>
	<p>White Warp_R EVO frontal Kit</p>	<p><b>Code</b>  <u>83363</u></p>
 <p>Ø81</p>	<p>White front adaptive flange for Warp EVO or Quantum EVO</p>	<p><b>Code</b>  <u>83393</u></p>



Black front adaptive flange for Warp EVO or Quantum EVO

**Code**  
83394



Gold Quantum\_R EVO frontal Kit

**Code**  
C-K400038



Copper Quantum EVO frontal Kit

**Code**  
C-K400039



Gold Warp\_R EVO frontal Kit

**Code**  
C-K400040



Copper Warp\_R EVO frontal Kit

**Code**  
C-K400041




Gold Vos\_R EVO frontal Kit

**Code**  
C-K400042



Copper Vos\_R EVO frontal Kit

**Code**  
C-K400043



Gold front adaptive flange for Warp EVO or Quantum EVO

**Code**  
C-K400044



Copper front adaptive flange for Warp EVO or Quantum EVO

**Code**

C-K400045