

### Downlights | arrayLED 0 W DC 700 mA | CRI 90 77331M30





Technical data		
Туре	Encasement with flange	
Installation position	Ceiling	
Installation environment	Indoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Medium Flood	
Light emission direction	downward	
Nominal power	0 W DC	
Input voltage range	700mA	
CCT / Tone	2700 K	
Colour rendering index	90 Ra	
C.C. / C.V.	CC	
Safety class	3	
IP	IP40	
Optical compartment IP	IP65	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	DALI - 1-10V	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	0.2 m	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.2 Kg	
Electrostatic discharge protection	No	


























Finishing casing		
Material	Technopolymer	
Colour	Black	
Processing	Coating	

Finishing diffuser		
Material	UV Resistant Polycarbonate	
Colour	transparent	

Finishing radiator		
Material	Die-cast Aluminium EN AB - 46100	
Colour	Aluminium	
Processing	Polishing	

Cables Electrification		
Cable connector	JST Quick connector Male + Female	

No

Surge protection

## Vos\_EVO



# Vos\_EVO | Downlights | Accessories **77331M30**

137 200	Outer casing installation position: ceiling; type of installation: masonry L=200mm, H=113mm, D=137mm. Material:polypropylene, colour:white.	<b>Code</b> 89373
370	Outer casing installation position: ceiling; type of installation: masonry L=370mm, H=120mm, D=200mm. Material:polypropylene, colour:white.	<b>Code</b> 89374
76  28	Outer casing installation position: ceiling; type of installation: drywall L=77.5mm, H=28mm, D=77.5m  Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.	<b>Code</b> 99849
	Optics Light distribution: medium wide flood,Cover material: uv resistant polycarbonate	<b>Code</b> 83372
	Optics Light distribution: medium flood,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate	<b>Code</b> 83371
	Optics Light distribution: spot,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate	<b>Code</b> 83370
	Anti-glare Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black.	<b>Code</b> 83367
	Diffuser Diffuser Type: elliptical filter	Code 83368

5.02.2025

## Vos\_EVO



# Vos\_EVO | Downlights | Accessories 77331M30

	Diffuser Diffuser Type: aesthetic filter	<b>Code</b> 83369
	White Quantum_R EVO frontal Kit	<b>Code</b> 83361
	Black Quantum_R EVO frontal Kit	<b>Code</b> 83362
	Black Vos_R EVO frontal Kit	<b>Code</b> 83366
	White Vos_R EVO frontal Kit	<b>Code</b> 83365
	Black Warp_R EVO frontal Kit	<b>Code</b> 83364
	White Warp_R EVO frontal Kit	<b>Code</b> 83363
Ø81	White front adaptive flange for Warp EVO or Quantum EVO	<b>Code</b> 83393



# Vos\_EVO | Downlights | Accessories 77331M30

(j) 68 Ø81	Black front adaptive flange for Warp EVO or Quantum EVO	<b>Code</b> 83394
	Gold Quantum_R EVO frontal Kit	<b>Code</b> C-K400038
	Copper Quantum EVO frontal Kit	<b>Code</b> C-K400039
	Gold Warp_R EVO frontal Kit	<b>Code</b> C-K400040
	Copper Warp_R EVO frontal Kit	<b>Code</b> C-K400041
	Gold Vos_R EVO frontal Kit	<b>Code</b> C-K400042
	Copper Vos_R EVO frontal Kit	<b>Code</b> C-K400043
Ø81	Gold front adaptive flange for Warp EVO or Quantum EVO	<b>Code</b> C-K400044

5.02.2025



Vos\_EVO | Downlights | Accessories 77331M30



Copper front adaptive flange for Warp EVO or Quantum EVO

Code

C-K400045