



# Quantum\_R EVO



Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90  
77346W45



Technical data	
Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Medium Flood
Light emission direction	downward
Nominal power	9 W DC
Source lumens	1119 lm
Input voltage range	700mA
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP40
Optical compartment IP	IP65
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.2 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Honey comb

## Finishing casing

Material	Technopolymer
Colour	White RAL 9003

## Finishing diffuser

Material	UV Resistant Polycarbonate
Colour	transparent

## Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Colour	Aluminium
Processing	Polishing

## Electronics



99147  
On/Off Driver 198~264V AC



99735  
Multi Power 198~264V AC / 180~275V DC



99733  
1-10V Multi Power 198~264V AC / 180~275V DC



C-E100012  
Push and Simply Dim - DALI-2 Controller



C-E100016  
Push and Simply Dim - DALI-2 Controller

## Cables Electrification

Cable connector	JST Quick connector Male + Female
-----------------	-----------------------------------



Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90 | Base **77346W45**

Single emission recessed downlights for indoor application. The warm white LED light source with a medium flood light distribution is composed of 1 arrayed LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1119 lm, with a 124.3 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white ral 9003 finish; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP40; the total weight is of 0.2 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 9 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be ceiling-mounted, with a 64 mm diameter hole (in plasterboard) with an outer casing, code 89374(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class E.

### Illuminotechnical Features

Light Output Ratio (LOR)	42 %
Source lumens	1119 lm
Delivered lumens	473 lm
Consumption	9 W
Luminaire efficacy	52 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	90 Ra

Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio



L70 B10 C0 112960h (at Tj 65 Ta 25 )

### UGR

UGR axial	12.4
UGR transversal	12.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	34°
Light distribution simmetry	Symmetrical





Outer casing  
installation position: ceiling; type of installation: masonry L=200mm, H=113mm, D=137mm.  
Material:polypropylene, colour:white.

**Code**  
89373



Outer casing  
installation position: ceiling; type of installation: masonry L=370mm, H=120mm, D=200mm.  
Material:polypropylene, colour:white.

**Code**  
89374



Optics  
Light distribution: medium wide flood,Cover material: uv resistant polycarbonate

**Code**  
83372



Optics  
Light distribution: medium flood,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate

**Code**  
83371



Optics  
Light distribution: spot,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate

**Code**  
83370



Anti-glare  
Anti-glare Type: honeycomb louvre.  
Material:Pom-C, colour:Black.

**Code**  
83367



Diffuser  
Diffuser Type: elliptical filter

**Code**  
83368



Diffuser  
Diffuser Type: aesthetic filter

**Code**  
83369



White Quantum\_R EVO frontal Kit

**Code**  
83361



Black Quantum\_R EVO frontal Kit

**Code**  
83362



Black Vos\_R EVO frontal Kit

**Code**  
83366



White Vos\_R EVO frontal Kit

**Code**  
83365



Black Warp\_R EVO frontal Kit

**Code**  
83364




White Warp\_R EVO frontal Kit

**Code**  
83363



White front adaptive flange for Warp EVO or Quantum EVO

**Code**  
83393



Black front adaptive flange for Warp EVO or Quantum EVO

**Code**  
83394



Quantum\_R EVO | Downlights | Accessories  
**77346W45**



Gold Quantum\_R EVO frontal Kit

**Code**  
C-K400038



Copper Quantum EVO frontal Kit

**Code**  
C-K400039



Gold Warp\_R EVO frontal Kit

**Code**  
C-K400040



Copper Warp\_R EVO frontal Kit

**Code**  
C-K400041



Gold Vos\_R EVO frontal Kit

**Code**  
C-K400042




Copper Vos\_R EVO frontal Kit

**Code**  
C-K400043



Gold front adaptive flange for Warp EVO or Quantum EVO

**Code**  
C-K400044



Copper front adaptive flange for Warp EVO or Quantum EVO

**Code**  
C-K400045

# Quantum\_R EVO

---



Quantum\_R EVO | Downlights | Accessories  
**77346W45**

---