## Cubit Pro

15

30

## Wall Lights | x powerLEDs 0 W DC - 3.2 W AC CRI 80 77416M30






60

12

Diffused 00

Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	powerLEDs	
Optics	Medium Flood	
Light emission direction	downward	
Nominal power	0 W DC	
Total Power	3.2 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	90 - 264 V AC	
CCT / Tone	2700 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
К	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.3 Kg	
Electrostatic discharge protection	Yes	
Surge protection	1 KV	

## EAE < < 🕅 🕐 🗄 🦳 KOB PES 🗉 🏹



Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating

i maning unuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	