Cubit Pro

15

30

Wall Lights | x powerLEDs 0 W DC - 3.2 W AC CRI 80




60

12

Diffused 00

Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Diffused
Light emission direction	downward
Nominal power 0 W DC	
Total Power	3.2 W
Nominal input voltage	220 - 240 V AC
Input voltage range	90 - 264 V AC
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.3 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV

EAE < < 🕅 🕐 🗄 🦳 KOB PES 🗉 🏹



	60
Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating

Finishing diffuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	