Cubit Pro



Wall Lights | x powerLEDs 0 W DC - 6.5 W AC CRI 80

77419N60









	Optic 30	Optic 60		
Technical data				
Туре			Surfa	се
Installation position			Wall lights	
Installation environment			Outdoor	
Light Source			LED	
Circuit structure			powe	rLEDs
Optics			Spot + Wide Flood	
Light emission direction			downward and upward	
Nominal power			0 W DC	
Total Power			6.5 W	
Nominal input voltage			220 - 240 V AC	
Input voltage range			180 - 264 V AC	
CCT / Tone			4000 K	
Colour rendering index			80 Ra	a
C.C. / C.V.			AC	
Safety class			1	
IP .			IP65	
IK			IK08	
Glow wire test			850°	
Direct mounting on normally flammable surfaces			Yes	
CE			Yes	
Driver included			Driver	
Dimmable article			No	
Directional			No	
Tilting			No	
Walk-over			No	
Drive-over			No	
Cable included			No	
Resin potting		No		
Type of light emission			Double emission	
Net weight			0.32 Kg	
Electrostatic discharge protection			Yes	
Surge protection			1 KV	


















Finishing casing			
Material	Die-cast Aluminium EN AB - 46100		
Colour	Black		
Processing	Open pore anodizing + Powder Coating		

Finishing diffuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	