## **Cubit Pro**



Wall Lights | x powerLEDs 0 W DC - 6.5 W AC CRI 80

## 77421N60







| Technical data                                 |                      |
|--|----------------------|
| Туре   | Surface              |
| Installation position                          | Wall lights          |
| Installation environment                       | Outdoor              |
| Light Source                                   | LED                  |
| Circuit structure                              | powerLEDs            |
| Optics   | Spot + Wide<br>Flood |
| Light emission direction                       | downward and upward  |
| Nominal power                                  | 0 W DC               |
| Total Power                                    | 6.5 W                |
| Nominal input voltage                          | 220 - 240 V AC       |
| Input voltage range                            | 180 - 264 V AC       |
| CCT / Tone                                     | 4000 K               |
| Colour rendering index                         | 80 Ra                |
| C.C. / C.V.                                    | AC                   |
| Safety class                                   | 1                    |
| IP   | IP65                 |
| IK   | IK08                 |
| Glow wire test                                 | 850°                 |
| Direct mounting on normally flammable surfaces | Yes                  |
| CE   | Yes                  |
| Driver included                                | Driver               |
| Dimmable article                               | No                   |
| Directional                                    | No                   |
| Tilting  | No                   |
| Walk-over                                      | No                   |
| Drive-over                                     | No                   |
| Cable included                                 | No                   |
| Resin potting                                  | No                   |
| Type of light emission                         | Double emission      |
| Net weight                                     | 0.32 Kg              |
| Electrostatic discharge protection             | Yes                  |
| Surge protection                               | 1 KV                 |
|  |                      |


















| Finishing casing |                                      |   |
|------------------|--------------------------------------|---|
| Material         | Die-cast Aluminium EN AB - 46100     |   |
| Colour           | Dark brown                           |   |
| Processing       | Open pore anodizing + Powder Coating |   |
| Processing       | Open pore anodizing + Powder Coating | 9 |

| Finishing diffuser |                              |  |
|--------------------|------------------------------|--|
| Material           | Extra clear glass - Tempered |  |
| Colour             | transparent                  |  |
| Processing         | Silk-screening               |  |