





Wall Lights | x powerLEDs 0 W DC - 6.5 W AC
CRI 80
77425W12



| Technical data | |
|--|-------------------------|
| Type | Surface |
| Installation position | Wall lights |
| Installation environment | Outdoor |
| Light Source | LED |
| Circuit structure | powerLEDs |
| Optics | Double Extra Wide Flood |
| Light emission direction | downward and upward |
| Nominal power | 0 W DC |
| Total Power | 6.5 W |
| Nominal input voltage | 220 - 240 V AC |
| Input voltage range | 180 - 264 V AC |
| CCT / Tone | 3000 K |
| Colour rendering index | 80 Ra |
| C.C. / C.V. | AC |
| Safety class | 1 |
| IP | IP65 |
| IK | IK08 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | Driver |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 0.32 Kg |
| Electrostatic discharge protection | Yes |
| Surge protection | 1 KV |

| Finishing casing | |
|--------------------|--------------------------------------|
| Material | Die-cast Aluminium EN AB - 46100 |
| Colour | Grey |
| Processing | Open pore anodizing + Powder Coating |
| Finishing diffuser | |
| Material | Extra clear glass - Tempered |
| Colour | transparent |
| Processing | Silk-screening |