## **Cubit Pro**



## Wall Lights | arrayLED 0 W DC - 15.5 W AC | CRI 80 77490N15







Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Asymmetric + Spot
Light emission direction	downward and upward
Nominal power	0 W DC
Total Power	15.5 W
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	0.83 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV

















Finishing casing		
Material	Die-cast Aluminium EN AB - 46100	
Colour	White	
Processing	Open pore anodizing + Powder Coating	

Finishing diffuser		
Material	Extra clear glass - Tempered	
Colour	transparent	
Processing	Silk-screening	