




Uplights | x powerLED 0 W DC 24 V | CRI 80  
81184M25



Technical data	
Type	Walk Over
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Elliptic Spot
Light emission direction	upward
Nominal power	0 W DC
Input voltage range	24 V
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP68
Installation limitations	Not for underwater use
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
C.V. - C.C. Converter	Converter 24V included
Dimmable article	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.2 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop - TVS

#### Finishing casing

Material	Die-cast Aluminium EN AB - 46100
Colour	black
Processing	Open pore anodizing + Powder Coating

#### Finishing diffuser

Material	Extra clear glass - Tempered
Colour	transparent

#### Finishing flange

Material	AISI 316L steel
Colour	steel
Processing	Brushing

#### Cables Electrification with converter

Cable connector	No
-----------------	----






Outer casing  
installation position: floor, land; type of installation: masonry L=97mm, H=76mm, D=97mm.  
Material:ABS Plastic, colour:black.

**Code**  
99650




Outer casing  
installation position: floor, land; type of installation: masonry L=97mm, H=78mm, D=97mm.  
Material:AISI 316 steel, colour:steel.

**Finish**  
 **Code**  
99560



Outer casing  
installation position: floor, land; type of installation: masonry L=73mm, H=76mm, D=97mm.  
Material:AISI 316 steel, colour:steel.

**Finish**  
 **Code**  
99855