




Downlights | 1 x powerLED 8 W DC 700 mA | CRI 90
81279M15



Technical data

Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	powerLED
Optics	Spot
Light emission direction	downward
Nominal power	8 W DC
Source lumens	689 lm
Input voltage range	700mA
CCT / Tone	2700 K
Colour rendering index	90 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP44
Optical compartment IP	IP65
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	Yes
total angle (horizontal plane)	360 °
total angle (vertical plane)	35 °
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.170 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.277 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	TVS

Finishing diffuser

Material	UV Resistant Polycarbonate
Colour	transparent

Finishing flange

Material	Die-cast Aluminium EN AB - 46100
Colour	Black
Processing	Powder coating

Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Colour	Aluminium
Processing	Polishing

Electronics

- 
99147
 On/Off Driver 198-264V AC (1 - 2 art.)

- 
99735
 Multi Power 198-264V AC / 180-275V DC (1 art.)

- 
99733
 1-10V Multi Power 198-264V AC / 180-275V DC (1 art.)

- 
C-E100012
 Push and Simply Dim - DALI-2 Controller (1 art.)

- 
C-E100016
 Push and Simply Dim - DALI-2 Controller (1 - 3 art.)



Downlights | 1 x powerLED 8 W DC 700 mA | CRI 90 | Base 81279M15


Single emission recessed downlights for indoor application. The super warm white LED light source with a spot light distribution is composed of 1 powerLED LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 689 lm, with a 86.1 lm/W nominal luminous efficacy.

The diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP44; the total weight is of 0.277 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W. The power supply cable is included and features a 0.170 m length.

The device features protection class III and can be ceiling-mounted, with a 70 mm diameter hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.13 0.11	E(0°) 18160 E(C90) 7.4° 8886 E(C0) 7.5° 8898
1.0	0.26 0.26	E(0°) 4540 E(C90) 7.4° 2221 E(C0) 7.5° 2225
1.5	0.39 0.39	E(0°) 2018 E(C90) 7.4° 987 E(C0) 7.5° 989
2.0	0.52 0.53	E(0°) 1135 E(C90) 7.4° 555 E(C0) 7.5° 556
2.5	0.65 0.66	E(0°) 726 E(C90) 7.4° 355 E(C0) 7.5° 356
3.0	0.78 0.79	E(0°) 504 E(C90) 7.4° 247 E(C0) 7.5° 247

— C0/C180 (Half-peak divergence: 15.0°)
— C90/C270 (Half-peak divergence: 14.8°)

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	60 %
Source lumens	689 lm
Delivered lumens	420 lm
Consumption	8 W
Luminaire efficacy	52 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Black Body Locus	On
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio

L70 B10 C0 247450h (at Tj 60 Ta 25)

UGR

UGR axial	11.2
UGR transversal	10.9
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	15°
Light distribution simmetry	Symmetrical

