





Uplights | 1 x powerLED 8 W DC 630 mA
RGBW - 4000

81321Q45



| Technical data | |
|--|------------------------|
| Type | Walk Over |
| Installation position | Floor |
| Installation environment | Outdoor |
| Light Source | LED |
| Circuit structure | powerLED |
| Optics | Medium Wide Flood |
| Light emission direction | upward |
| Nominal power | 8 W DC |
| Input voltage range | 630mA |
| CCT / Tone | RGBW - 4000 K |
| C.C. / C.V. | CC |
| Safety class | 3 |
| IP | IP68 |
| Installation limitations | Not for underwater use |
| IK | IK10 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | No |
| Dimmable article | Yes |
| Directional | No |
| Tilting | No |
| Walk-over | Yes |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 0.2 m |
| Resin potting | Yes |
| Type of light emission | Single emission |
| Net weight | 0.5 Kg |
| Electrostatic discharge protection | No |
| Surge protection | No |
| Product technological characteristics | Acquastop |

Finishing casing

| | |
|------------|--------------------------------------|
| Material | Die-cast Aluminium EN AB - 46100 |
| Colour | black |
| Processing | Open pore anodizing + Powder Coating |

Finishing flange

| | |
|------------|-----------------|
| Material | AISI 316L steel |
| Colour | steel |
| Processing | Brushing |

Electronics



C-E500011
DMX-RDM - NFC Multi Channel 4ch. 19~50V DC (1 art.)

Cables Electrification

Cable connector Male Plug 4 pin M12

IP (locked condition) 67

Cable connector Female Socket 4 Pin M12

Lumen RGBW

| N. Led | Red | Green | Blue | white |
|--------|-------|--------|-------|--------|
| 1 | 74 lm | 121 lm | 21 lm | 153 lm |



Uplights | 1 x powerLED 8 W DC 630 mA | RGBW - 4000
81321Q45

Single emission uplights for outdoor application. The RGBW - 4000 K LED light source with a medium wide flood light distribution is composed of 1 powered LEDs with CCT of RGB-W 4000 K.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating. The ingress protection degree is IP68; the total weight is of 0.5 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99651 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class G.

| | |
|--|-------------|
| Standard Operating Ambient Temperature | -20 / +50°C |
|--|-------------|

| | |
|-----------------------------------|------|
| Ordinary temperature on the glass | 40°C |
|-----------------------------------|------|

LED Life / Failure Ratio


L70 B10 C0 202460h (at Tj 60 Ta 25)



| | | | |
|--|---|--|-------------------------------------|
| | <p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m) Length 5000 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p> | <p>Code <u>89190</u></p> | |
| | <p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m) Length 5000 mm; insulation double; cable gland: no.</p> | <p>Code <u>98149</u></p> | |
| | <p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m) Length 10000 mm; insulation double; cable gland: no.</p> | <p>Code <u>89188</u></p> | |
| | <p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m) Length 1500 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p> | <p>Code <u>99216</u></p> | |
| | <p>Cable and connector - Extension cable Length 1000 mm; insulation double; cable gland: no.</p> | <p>Code <u>98437</u></p> | |
| | <p>Cable and connector Length 1500 mm; insulation double; section 0.5 mm²; cable gland: no; external diameter: 5.4 mm; colors: white - black - blue - brown.</p> | <p>Code <u>98476</u></p> | |
| | <p>Cable and connector Length 5000 mm; insulation double; section 0.5 mm²; cable gland: no; external diameter: 5.4 mm; colors: white - black - blue - brown.</p> | <p>Code <u>98477</u></p> | |
| | | <p>Outer casing installation position: floor, land; type of installation: masonry L=114mm, H=76mm, D=114mm. Material:ABS Plastic, colour:black.</p> | <p>Code <u>99651</u></p> |




Orma_I | Uplights | Accessories
81321Q45



Dimmer
RF Remote controller

Code
C-E700003



RF remote control

Code
C-W600001