



Uplights | 1 x powerLED 8 W DC 630 mA  
RGBW - 3000

81321V06



| Technical data                                 |                        |
|--|------------------------|
| Type   | Walk Over              |
| Installation position                          | Floor                  |
| Installation environment                       | Outdoor                |
| Light Source                                   | LED                    |
| Circuit structure                              | powerLED               |
| Optics   | Ultra Spot             |
| Light emission direction                       | upward                 |
| Nominal power                                  | 8 W DC                 |
| Input voltage range                            | 630mA                  |
| CCT / Tone                                     | RGBW - 3000 K          |
| C.C. / C.V.                                    | CC                     |
| Safety class                                   | 3                      |
| IP   | IP68                   |
| Installation limitations                       | Not for underwater use |
| IK   | IK10                   |
| Glow wire test                                 | 850°                   |
| Direct mounting on normally flammable surfaces | Yes                    |
| CE   | Yes                    |
| Driver included                                | No                     |
| Dimmable article                               | Yes                    |
| Directional                                    | No                     |
| Tilting  | No                     |
| Walk-over                                      | Yes                    |
| Drive-over                                     | No                     |
| Cable included                                 | Yes                    |
| Cable length                                   | 0.2 m                  |
| Resin potting                                  | Yes                    |
| Type of light emission                         | Single emission        |
| Net weight                                     | 0.5 Kg                 |
| Electrostatic discharge protection             | No                     |
| Surge protection                               | No                     |
| Product technological characteristics          | Acquastop              |

#### Finishing casing

|            |                                      |
|------------|--------------------------------------|
| Material   | Die-cast Aluminium EN AB - 46100     |
| Colour     | black                                |
| Processing | Open pore anodizing + Powder Coating |

#### Finishing flange

|            |                 |
|------------|-----------------|
| Material   | AISI 316L steel |
| Colour     | steel           |
| Processing | Brushing        |

#### Electronics



C-E500011  
DMX-RDM - NFC Multi Channel 4ch. 19~50V DC (1 art.)

#### Cables Electrification

Cable connector Male Plug 4 pin M12

IP (locked condition) 67

Cable connector Female Socket 4 Pin M12

#### Lumen RGBW

| N. Led | Red   | Green  | Blue  | white  |
|--------|-------|--------|-------|--------|
| 1      | 74 lm | 121 lm | 21 lm | 122 lm |



Uplights | 1 x powerLED 8 W DC 630 mA | RGBW - 3000  
**81321V06**

Single emission uplights for outdoor application. The RGBW - 3000 K LED light source with a ultra spot light distribution is composed of 1 powered LEDs with CCT of RGB-W 3000 K.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating. The ingress protection degree is IP68; the total weight is of 0.5 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99651 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

#### Energy efficiency class

This product contains a light source of energy efficiency class G.

|  |             |
|--|-------------|
| Standard Operating Ambient Temperature | -20 / +50°C |
|--|-------------|

|                                   |      |
|-----------------------------------|------|
| Ordinary temperature on the glass | 40°C |
|-----------------------------------|------|

#### LED Life / Failure Ratio


L70 B10 C0 202460h (at Tj 60 Ta 25 )



|  |   |  |                                     |
|--|---|--|-------------------------------------|
|  | <p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m)<br/>Length 5000 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p>            | <p><b>Code</b><br/><u>89190</u></p>  |                                     |
|  | <p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m)<br/>Length 5000 mm; insulation double; cable gland: no.</p>   | <p><b>Code</b><br/><u>98149</u></p>  |                                     |
|  | <p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m)<br/>Length 10000 mm; insulation double; cable gland: no.</p>   | <p><b>Code</b><br/><u>89188</u></p>  |                                     |
|  | <p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m)<br/>Length 1500 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p>          | <p><b>Code</b><br/><u>99216</u></p>  |                                     |
|  | <p>Cable and connector - Extension cable<br/>Length 1000 mm; insulation double; cable gland: no.</p>  | <p><b>Code</b><br/><u>98437</u></p>  |                                     |
|  | <p>Cable and connector<br/>Length 1500 mm; insulation double; section 0.5 mm<sup>2</sup>; cable gland: no; external diameter:<br/>5.4 mm; colors: white - black - blue - brown.</p> | <p><b>Code</b><br/><u>98476</u></p>  |                                     |
|  | <p>Cable and connector<br/>Length 5000 mm; insulation double; section 0.5 mm<sup>2</sup>; cable gland: no; external diameter:<br/>5.4 mm; colors: white - black - blue - brown.</p> | <p><b>Code</b><br/><u>98477</u></p>  |                                     |
|  |   | <p><b>Outer casing</b><br/>installation position: floor, land; type of installation: masonry L=114mm, H=76mm,<br/>D=114mm.<br/>Material:ABS Plastic, colour:black.</p> | <p><b>Code</b><br/><u>99651</u></p> |




Orma\_I | Uplights | Accessories  
**81321V06**



Dimmer  
RF Remote controller

**Code**  
C-E700003



RF remote control

**Code**  
C-W600001