Archiline_F Anti-glare



Lines | x powerLED 0 W DC - 20.5 W AC | CRI 80


























45		
_	511	45
102	82	45

Technical data	
Туре	Frameless
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Spot
Light emission direction	upward
Nominal power	0 W DC
Total Power	20.5 W
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	5000 Kg
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	2.8 Kg
Electrostatic discharge protection	4 KV
Surge protection	6 KV
Optics technology	Dark light
Product technological characteristics	Acquastop - TVS

Finishing casing	
Material	Aluminium 6060
Colour	Anodised Black
Processing	15 μm Anodizing

Finishing diffuser			
Material	Extra clear glass - Tempered		
Colour	transparent		
Processing	Silk-screening		

Cables Electrification+signal				
Cable connector	Female Socket 5 Pin			
IP (locked condition)	68			
Cable connector	Male Plug 5 Pin			

Archiline_F Anti-glare



linealight.com

Archiline_F Anti-glare | Lines | Accessories **81595W15**

50 46 331 331 70 511	Outer casing installation position: floor; type of installation: masonry L=511mm, H=140mm, D=75mm Material:Aluminium 6060, colour:Anodised Black, processing:15 µm Anodizing.	Code 98725
	Key	Code 98957
	Cable and connector Length 5000 mm.	Code 99822
	Cable and connector Length 1000 mm.	Code 99823
	Cable and connector Length 5000 mm.	Code 99824
	Cable and connector Length 10000 mm.	Code 99825
	Cable and connector Length 1000 mm.	Code 99826