


# Alux Pro



Ceiling Downlights | 220-240 V  
32 topLED 65 W DC - 70 W AC | CRI 80  
**81777N60**



Technical data	
Type	Surface
Installation position	Ceiling
Installation environment	Outdoor
Light Source	LED
Circuit structure	topLED
Optics	Wide Flood
Light emission direction	downward
Nominal power	65 W DC
Total Power	70 W
Source lumens	10538 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK06
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	No
Type of light emission	Single emission
Net weight	3.2 Kg
Electrostatic discharge protection	Yes
Surge protection	5 KV

## Finishing casing

Material	Aluminium 6060
Colour	Anodised Aluminum
Processing	20 µm anodizing

## Finishing diffuser

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening



Ceiling Downlights | 220-240 V | 32 topLED 65 W DC - 70 W AC | CRI 80 | Base 81777N60

### Energy efficiency class

This product contains 2 light sources of energy efficiency class D.

### Illuminotechnical Features

Light Output Ratio (LOR)	91 %
Source lumens	10538 lm
Delivered lumens	9618 lm
Consumption	70 W
Luminaire efficacy	137 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C

### LED Life / Failure Ratio

L70 B20 C10 108000h (at Tj 65 Ta 25 )

### UGR

UGR axial	21.6
UGR transversal	22.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	52°
Light distribution symmetry	Symmetrical


Single emission ceiling downlights for outdoor application. The natural white LED light source with a wide flood light distribution is composed of 32 powered LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 10538 lm, with a 162.1 lm/W nominal luminous efficacy.

The device body is made of aluminium 6060 and features a anodised aluminum finish, processed by means of 20 µm anodizing; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP65; the total weight is of 3.2 kg.

The total absorbed power is 70 W. The power supply cable is included and features a 1 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.48 0.50	E(0°) 39753 E(C90) 25.8° 14516 E(C0) 26.5° 14329
1.0	0.97 1.00	E(0°) 9938 E(C90) 25.8° 3629 E(C0) 26.5° 3582
1.5	1.45 1.50	E(0°) 4417 E(C90) 25.8° 1613 E(C0) 26.5° 1592
2.0	1.93 1.98	E(0°) 2485 E(C90) 25.8° 907 E(C0) 26.5° 896
2.5	2.42 2.49	E(0°) 1590 E(C90) 25.8° 581 E(C0) 26.5° 573
3.0	2.90 2.99	E(0°) 1104 E(C90) 25.8° 403 E(C0) 26.5° 398

— C0/C180 (Half-peak divergence: 53.0°)  
— C90/C270 (Half-peak divergence: 51.6°)



#### Cable

Type of cable power + signal cable; Length 1000 mm; insulation double without shielding; section 2.5 mm<sup>2</sup>; cable gland: no; colors: black - blue - grey - brown - yellow-green.

#### Code

83239