



Ceiling Downlights | 198-264 V
1 arrayLED 25 W DC - 28 W AC | CRI 80
81880N60



Technical data	
Type	Surface
Installation position	Ceiling
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Wide Flood
Light emission direction	downward
Nominal power	25 W DC
Total Power	28 W
Source lumens	4116 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	2.8 Kg
Electrostatic discharge protection	Yes
Surge protection	5 KV
Optics technology	Set-back low glare optics

Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating
Finishing diffuser	
Material	Extra clear glass
Colour	transparent
Processing	Silk-screening

Ceiling Downlights | 198-264 V | 1 arrayLED 25 W DC - 28 W AC | CRI 80 | Base
81880N60

Single emission ceiling downlights for outdoor application. The natural white LED light source with a wide flood light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 4116 lm, with a 164.6 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a dark brown finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass with a silk-screening treatment. The ingress protection degree is IP65; the total weight is of 2.8 kg.

The total absorbed power is 28 W.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	59 %
Source lumens	4116 lm
Delivered lumens	2452 lm
Consumption	28 W
Luminaire efficacy	87 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra

Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25)

UGR

UGR axial	19.9
UGR transversal	19.9
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	54°
Light distribution simmetry	Symmetrical



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.51 0.53	E(0°) 13117 E(C90) 27.2° 4624 E(C0) 28.0° 4536
1.0	1.03 1.06	E(0°) 3279 E(C90) 27.2° 1156 E(C0) 28.0° 1134
1.5	1.54 1.60	E(0°) 1457 E(C90) 27.2° 514 E(C0) 28.0° 504
2.0	2.06 2.13	E(0°) 820 E(C90) 27.2° 289 E(C0) 28.0° 284
2.5	2.57 2.66	E(0°) 525 E(C90) 27.2° 185 E(C0) 28.0° 181
3.0	3.08 3.19	E(0°) 264 E(C90) 27.2° 128 E(C0) 28.0° 126

— C0/C180 (Half-peak divergence: 56.0°)
 — C90/C270 (Half-peak divergence: 54.4°)