

Projectors | 176-264 V 1 arrayLED 27 W DC - 30 W AC | CRI 98









Technical data	
Туре	Track
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Shaper Long Distance
Light emission direction	frontal
Nominal power	27 W DC
Total Power	30 W
Source lumens	3851 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	176 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	98 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI-2 - PUSH DIM
Directional	Swivelling
total angle (vertical plane)	90 °
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.45 Kg
Electrostatic discharge protection	Yes
Surge protection	2 KV




















Finishing casing	9
Material	Die-cast Aluminium EN AB - 46100
Colour	White
Processing	Powder coating



Projectors | 176-264 V | 1 arrayLED 27 W DC - 30 W AC | CRI 98 | Base **82072N66** 


Single emission projectors for indoor application. The natural white LED light source with a shaper long distance light distribution is composed of 1 arrayled LEDs with CCT of 4000 K and a CRI 98; the source luminous flux is 3851 lm, with a 142.6 lm/W nominal luminous efficacy.


The device body is made of die-cast aluminium en ab - 46100 and features a white finish, processed by means of powder coating. The ingress protection degree is IP20; the total weight is of 1.45 kg.

The total absorbed power is 30 W.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





#### Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features	
Light Output Ratio (LOR)	9 %
Source lumens	3851 lm
Delivered lumens	369 lm
Consumption	30 W
Luminaire efficacy	12 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	98 Ra
Black Body Locus	On
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	45°C


#### LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25)

UGR	
UGR axial	-5.3
UGR transversal	-5.3
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
C0/C180 optics	14°
Light distribution simmetry	Symmetrical

#### COLOR VECTOR GRAPHIC







### Pound Shaper\_distance | Projectors | Accessories **82072N66**

and a second	95 8 31 148	Power supply - White Right power supply header (9001/W) Material:PC, colour:white.	<b>Code</b> 81033
	95 8 31 148	Power supply - White left power supply header (9002/W) Material:PC, colour:white.	<b>Code</b> 81036
	95 95 31 148	Power supply - Black left power supply header (9002/B) Material:PC, colour:black.	<b>Code</b> 81037
	95 31 148	Power supply - Black Right power supply header (9001/B) Material:PC, colour:black.	<b>Code</b> 81034
STUCCEI		Closing cap - White end cap 9004/W Material:PC, colour:white.	<b>Code</b> 80999
		Closing cap - Black end cap 9004/B Material:PC, colour:black.	<b>Code</b> 81000
STUCCERI		Closing cap - Recessed white end cap 9004-R/W Material:PC, colour:white.	<b>Code</b> 81002
	9	Closing cap - Recessed black end cap 9004-R/B	<b>Code</b> 81003

Material:PC, colour:black.



Pound Shaper\_distance | Projectors | Accessories **82072N66** 

0	3 8 9 8 5 8 5 8 5 8 5 8 5 8 5 8 5 8 5 8 5	Closing cap - White gasket (S-9001/115-W) Material:white.		<b>Code</b> 81084
	3 3 5 4 9 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Closing cap - Black gasket (S-9001/115-B)  Material:black, colour:black.		<b>Code</b> 81085
		Ceiling rose - 1.5m white pendant luminaires kit + bracket (9000-KIT5-1,5-W)  Material:plastic, colour:white.		<b>Code</b> 81012
*	Ø 32	Ceiling rose - 1.5m black pendant luminaires kit + bracket ((9000-KIT5-1,5-B) Material:plastic, colour:black.		<b>Code</b> 81014
	92.32. 92.32. 93.32. 94. 95. 95. 96. 97. 98. 98. 98. 98. 98. 98. 98. 98	Ceiling rose - 5m white pendant luminaires kit + bracket (9000-KIT5-5-W)  Material:plastic, colour:white.		<b>Code</b> 81013
*		Ceiling rose - 5m black pendant luminaires kit + bracket (9000-KIT5-5-B) Material:plastic, colour:black.		<b>Code</b> 81015
	2 1 0	Bracket - Anodized fixing bracket (S-9000/131) L=35mm, H=14mm, D=24mm. Material:Aluminium, colour:translucent.	Finish Anod. Al.	<b>Code</b> 81086

Bracket - Anodized stiffening bracket (S-9000/333)

 ${\it Material:} A luminium, \ colour: Anodised \ A luminum, \ processing: Anodisation.$ 

L=180mm, H=24mm, D=26mm.

Code

81024

Finish



#### Pound Shaper\_distance | Projectors | Accessories 82072N66





Bracket - White stiffening bracket (S-9000/333-W) L=180mm, H=24mm, D=20mm.

Material: Aluminium, colour: white RAL 9010, processing: Coating.

**Finish** White

Code

81025





Bracket - Black stiffening bracket (S-9000/333-B) L=180mm, H=24mm, D=20mm.

Material: Aluminium, colour: black RAL 9005, processing: Coating.

**Finish** 

Code

81026





Bracket - White fixing braket (S-9000/131-W)

L=35mm, H=14mm, D=24mm.

Material: Aluminium, colour: white, processing: Coating.

**Finish** White

Code

81087





Bracket - Black fixing braket (S-9000/131-B)

L=35mm, H=14mm, D=24mm.

Material: Aluminium, colour: Black, processing: Coating.

**Finish** 

Code

81088





Junction - White electrical junction - internal (9003/W)

Type linear.


Material:PC, colour:white.

Finish White

Code

81039





Junction - Black electrical junction - internal (9003/B)

Type linear.

Material:PC, colour:black.

**Finish** 

Code

81040






Junction - White power supply junction - central (9010/W)

Material:PC, colour:white.

Finish

Code 81042





Junction - White L junction - internal (9011/W)

Type linear.

Material:PC, colour:white.


Finish White

Code



### Pound Shaper\_distance | Projectors | Accessories **82072N66**





Junction - White L junction - external (9012/W)

Type linear.

Material:PC, colour:white.

Finish White **Code** 81048





Junction - Flexible white junction (9018/W)

Type flexible curve.

Material:PC, colour:white.

Finish White **Code** 81066





Junction - White X junction (9017/W)


Type linear.

Material:PC, colour:white.

Finish White Code

81063





Junction - Left white T junction - external (9013/W)


Type linear

Material:PC, colour:white.

Finish White Code

81051






Junction - Right white T junction - external (9014/W)

Type linear.

Material:PC, colour:white.

Finish White **Code** 81054






Junction - Left white T junction - internal (9015/W)

Type linear.

Material:PC, colour:white.

Finish White **Code** 81057



Junction - Right White T junction - internal (9016/W)

Type linear

Material:PC, colour:white.

Finish

**Code** 81060





Junction - Black power supply junction - centrale (9010/B)

Type linear.

Material:PC, colour:black.


Finish

Code



### Pound Shaper\_distance | Projectors | Accessories **82072N66**





Junction - Black L junction - internal (9011/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81046





Junction - Black L junction - external (9012/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81049





Junction - Flexible black junction (9018/B)

Type flexible curve.

Material:PC, colour:black.

Finish

Code

81067





Junction - Black X junction (9017/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81064





Junction - Black left T junction - external (9013/B)

Type linear.

Material:PC, colour:black.

Finish

**Code** 81052






Junction - Right black T junction - external (9014/B)

Type linear.

Material:PC, colour:black.

Finish

**Code** 81055



Junction - Left black T junction - internal (9015/B)

Type linear


Material:PC, colour:black.

Finish

Code

81058





Junction - Right black T junction - internal (9016/B)

Type linear.

Material:PC, colour:black.

Finish

Code



		Suspensions - 1.5m white pendant luminaires kit (9000-KIT3-1,5-W)  Material:plastic, colour:white.	<b>Code</b> 81006
		Suspensions - 5m white pendant luminaires kit (9000-KIT3-5-W)  Material:plastic, colour:white.	<b>Code</b> 81007
	32. \$\frac{1}{2}\$ \$	Suspensions - 1.5m black pendant luminaires kit (9000-KIT3-1,5-B)  Material:plastic, colour:black.	<b>Code</b> 81008
*	32. \$\frac{1}{2}\$ \$\frac{1}{2}\$ \$\frac{1}{2	Suspensions - 5m black pendant luminaires kit (9000-KIT3-5-B)  Material:plastic, colour:black.	<b>Code</b> 81009
		Suspensions - White rigid suspension clip (S-9000-P2-W)  Material:plastic, colour:white.	<b>Code</b> 81018
		Suspensions - Black rigid suspension clip (S-9000-P2-B)  Material:plastic, colour:black.	<b>Code</b> 81019
		Suspensions - White rigid suspension 1m (S-9000-P3-W) Material:plastic, colour:white.	<b>Code</b> 81021
		Suspensions - Black rigid suspension 1m (S-9000-P3-B)  Material:plastic, colour:black.	<b>Code</b> 81022



	100000000000000000000000000000000000000	Cable cover - White recessed cover (S-9001-R/6-W) Material:PC, colour:white.	<b>Code</b> 81069
	• EXISTS •	Cable cover - White cover for recessed junction (S-9010-R/6-W)  Material:PC, colour:white.	<b>Code</b> 81072
	O (AZENTADO	Cable cover - White cover for recessed L junction (S-9011-R/6-W) Material:PC, colour:white.	<b>Code</b> 81075
- 1000	+ (1)1/11 +	Cable cover - White cover for recessed T junction (S-9013-R/6-W)  Material:PC, colour:white.	<b>Code</b> 81078
- 1-1-1-1	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Cable cover - White cover for recessed X junction (S-9017-R/6-W)  Material:PC, colour:white.	<b>Code</b> 81081
	### T T T T T T T T T T T T T T T T T T	Cable cover - Black recessed cover (S-9001-R/6-B) Material:PC, colour:black.	<b>Code</b> 81070
	• E318% •	Cable cover - Black cover for recessed junction (S-9010-R/6-B)  Material:PC, colour:black.	<b>Code</b> 81073
	0 (313531)0	Cable cover Material:PC, colour:black.	<b>Code</b> 81076



	+ (c1)Y(x) +	Cable cover - Black cover for recessed T junction (S-9013-R/6-B)  Material:PC, colour:black.	<b>Code</b> 81079
	0 (12 May 0)	Cable cover - Black cover for recessed X junction (S-9017-R/6-B)  Material:PC, colour:black.	<b>Code</b> 81082
		Cable cover Material:white.	<b>Code</b> 83249
		Cable cover Material:black, colour:black.	<b>Code</b> 83250
5.00	2 13.5 2 10 10 10 10 10 10 10 10 10 10 10 10 10	White three-phase/DALI adapter (9009/W)	<b>Code</b> 81094
	S 100	White three-phase adapter (9009-4/W)	<b>Code</b> 81091
		Black three-phase/DALI adapter (9009/B)	<b>Code</b> 81095
		Black trhee-phase adapter (9009-4/B)	<b>Code</b> 81093



Pound Shaper\_distance | Projectors | Accessories **82072N66** 

		Tool - Cutter S-9000/T		<b>Code</b> 81005
5		Tool - Gobo holder  Material:Aluminium, colour:black, processing:Anodisation.		<b>Code</b> 99853
	31.4 (1) (2) (3) (4) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	Track - Three-phase Recessed White DALI Track, 1 m (9000-1/W-R) Length: 1000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.	Finish White	<b>Code</b> 80990
	31.4 (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	Track - Three-phase Recessed White DALI Track, 2 m (9000-2/W-R) Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.	Finish White	<b>Code</b> 80991
		Track - Trhee-phase Recessed White DALI Track, 3 m ( 9000-3/W-R) Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.	Finish White	<b>Code</b> 80992
		Track - Three-phase Recessed Grey DALI Track, 1 m (9000-1/B-R) Length: 1000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.	<b>Finish</b> Black	<b>Code</b> 80993
		Track - Three-phase Recessed Black DALI Track, 2 m (9000-1/B-R) Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.	Finish Black	<b>Code</b> 80994
		Track - Three-phase Recessed Black DALI Track, 3 m (9000-3/B-R) Length: 3000mm; Type of track: Standard.	Finish Black	<b>Code</b> 80995

 $Material: Aluminium,\ colour: Black,\ processing: Coating.$ 



37.8 30.7	Trock	Finish White	<b>Code</b> 83336
37.8 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0	Track Length: 2000mm; Type of track: Standard. Material:Aluminium, colour:White, processing:Coating.	Finish White	<b>Code</b> 83337
37.8 30.7	Track	<b>Finish</b> White	<b>Code</b> 83338
37.8	Track	Finish Black	<b>Code</b> 83339
37.8	Track	Finish Black	<b>Code</b> 83340
37.8	Track Length: 3000mm; Type of track: Standard. Material:Aluminium, colour:Black, processing:Coating.	Finish Black	<b>Code</b> 83341
124	Electronic accessory - TWIL-DALI controller for devices with DALI protocol installed on three-phase track. installation position: ceiling L=90mm, H=124mm, D=45mm. Material:ABS Plastic, colour:black.		Code C-E700008