

Ribbon PRO




LED Strip | 400 topLED 18 W DC 24 V | 3.6 W/m
550.8 Lm/m | CRI >90

82125



Technical data	
Length	5000 mm
Minimum cut	100 mm
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	18 W DC
Source lumens	2754 lm
Input voltage range	24V
CCT / Tone	4000 K
Colour rendering index	>90 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.3 m
Resin potting	No
Type of light emission	Single emission
Length	5000 mm
Net weight	0.09 Kg
Electrostatic discharge protection	No
Surge protection	No



Finishing casing

Colour	white
--------	-------

Electronics

	99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 art.)
--	-----------------------------------------------------------------

	99332 1-10V Controller (1 - 8 art.)
--	----------------------------------------

	99374 On/Off Driver 198~264V AC / 176~275V DC 75 W (1 - 4 art.)
--	--------------------------------------------------------------------

	83333 Push and Simply Dim - DALI-2 Controller (1 - 8 art.)
--	---------------------------------------------------------------

	C-E400002 Push and Simply Dim - DALI-2 Controller (1 - 13 art.)
--	--------------------------------------------------------------------

Cables Electrification

Max cable length	300 mm
------------------	--------



LED Strip | 400 topLED 18 W DC 24 V | 3.6 W/m | 550.8 Lm/m | CRI >90 | Base
82125

Single emission led strip for indoor application. The natural white LED light source with a diffused light distribution is composed of 400 topLED LEDs with CCT of 4000 K and a CRI >90; the source luminous flux is 2754 lm, with a 153.0 lm/W nominal luminous efficacy.

The device body and features a white finish. The ingress protection degree is IP20; the total weight is of 0.09 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 18 W. The power supply cable is included and features a 0.3 m length.

The device features protection class III and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class D.



Illuminotechnical Features


Light Output Ratio (LOR)	100 %
Source lumens	2754 lm
Delivered lumens	2754 lm
Consumption	18 W
Luminaire efficacy	153 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Standard Operating Ambient Temperature	-20 / +55°C

UGR

UGR axial	26.9
UGR transversal	27.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	116°
C0/C180 optics	120°
Light distribution symmetry	Symmetrical 2 axis



Distance [m]	Cone diameter [m]	E(0°)	E(C90)	E(C0)
0.5	1.60 1.75	3533	263	217
1.0	3.20 3.49	883	66	54
1.5	4.80 5.24	393	29	24
2.0	6.40 6.98	221	16	14
2.5	8.00 8.73	141	11	9
3.0	9.60 10.48	98	7	6

Distance [m] Cone diameter [m] Illuminance [lx]

— C0/C180 (Half-peak divergence: 120.4°)
— C90/C270 (Half-peak divergence: 116.0°)

Ribbon PRO



LED Strip | 400 topLED 18 W DC 24 V | 3.6 W/m | 550.8 Lm/m | CRI >90
82125

Components

		LUNO_20/27 - Profili Modular	Code <u>C-K100017</u>
		LUNO_20/27	Code <u>C-K100018</u>
		Rive_17/16 - Profili Modular	Code <u>C-K100015</u>
		Rive_17/16 - Profili Modular	Code <u>C-K100016</u>
		Cela_18/18 - Profili Modular	Code <u>C-K100019</u>
		Cela_18/18 - Profili Modular	Code <u>C-K100020</u>
		Tabulo_35/14 - Profili Modular	Code <u>C-K100025</u>
		Fylo+ Recessed_2	Code <u>65007 - 65006</u>



Ribbon PRO



LED Strip | 400 topLED 18 W DC 24 V | 3.6 W/m | 550.8 Lm/m | CRI >90


82125

Components



Fylo+ Recessed_4

Code
65010 - 65009




Fylo+ Recessed_1

Code
65027 - 65028




Fylo+ Surface_1

Code
65015 - 65016




Fylo+ Surface_2

Code
65018 - 65019




Fylo+ Surface_3

Code
65021 - 65022



Fylo+ Surface_4

Code
65024 - 65025



Fylo+ Recessed_5

Code
65013 - 65012



Fylo+ Recessed_3

Code
65004 - 65003

Ribbon PRO



LED Strip | 400 topLED 18 W DC 24 V | 3.6 W/m | 550.8 Lm/m | CRI >90
82125

Components



















Fylo+ Direct_1

















Code

65180 - 65181



 <p>5x</p>	 <p>25 30 6,8</p>	<p>Springs for recessing - 5 pieces</p>	<p>Code 98420</p>
	 <p>2,5 18 2000</p>	<p>Diffuser Diffuser Type: opaline diffuser. Material:PC, colour:opaline.</p>	<p>Finish Opaline Code 98395</p>
	 <p>15 2000</p>	<p>Diffuser</p>	<p>Code 98941</p>
	 <p>15 2000</p>	<p>Diffuser</p>	<p>Code 98942</p>
	 <p>15 2000</p>	<p>Diffuser - Opaline Diffuser</p>	<p>Code 98943</p>
	 <p>24 2000</p>	<p>Diffuser</p>	<p>Code 98898</p>
	 <p>24 2000</p>	<p>Diffuser</p>	<p>Code 98899</p>
	 <p>24 2000</p>	<p>Diffuser</p>	<p>Code 98900</p>



		Diffuser	Code 98917
		Diffuser	Code 98925
		Diffuser Material:PC, colour:black.	Finish Black Code 83132
		Diffuser Material:PC, colour:opaline.	Finish Opaline Code C-K200001
		Diffuser Material:PC, colour:black.	Finish Black Code C-K200002
		Diffuser Material:PC, colour:opaline.	Finish Opaline Code C-K200003
		Diffuser Material:PC, colour:black.	Finish Black Code C-K200004
		Diffuser Material:PC, colour:opaline.	Finish Opaline Code C-K200005



Diffuser
Material:PC, colour:opaline.

Finish
Opaline **Code**
C-K200007



Diffuser
Material:PC, colour:black.

Finish
Black **Code**
C-K200009



Closing cap

Code
98418



Closing cap - Closing cap
Material:PC, colour:white.

Code
98892



Closing cap

Code
98928



Closing cap

Code
98896



Closing cap

Code
98902



Closing cap
Material:Aluminium, colour:translucent.

Code
98907



		<p>Closing cap Material:PC, colour:white.</p>	<p>Code <u>98922</u></p>
		<p>Closing cap Material:PC, colour:white.</p>	<p>Code <u>98918</u></p>
		<p>Closing cap Material:PC, colour:black.</p>	<p>Code <u>83133</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400023</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400019</u></p>
		<p>Closing cap Material:ABS Plastic, colour:black.</p>	<p>Code <u>C-V400020</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400021</u></p>
		<p>Closing cap Material:ABS Plastic, colour:black.</p>	<p>Code <u>C-V400022</u></p>



		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400025</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400027</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400029</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400031</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400033</u></p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code <u>C-V400035</u></p>
		<p>Closing cap Material:ABS Plastic, colour:black.</p>	<p>Code <u>C-V400036</u></p>
		<p>Closing cap Material:ABS Plastic, colour:black.</p>	<p>Code <u>C-V400038</u></p>



		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code C-V400037</p>
		<p>Closing cap Material:plastic, colour:grey.</p>	<p>Code C-V400041</p>
		<p>Bracket - Mounting bracket L=19mm, H=8mm, D=9mm. Material:Iron, colour:zinc, processing:Washing.</p>	<p>Code 98944</p>
		<p>Bracket L=9mm, H=8.8mm, D=21.8mm. Material:Iron, colour:translucent, processing:Washing.</p>	<p>Code 98931</p>
		<p>Bracket L=22mm, H=21.5mm, D=16.4mm. Material:PC, colour:transparent.</p>	<p>Finish Transp.</p> <p>Code 98904</p>
		<p>Bracket L=12mm, H=15mm, D=30mm. Material:PC, colour:white.</p>	<p>Finish White</p> <p>Code 98901</p>
		<p>Profile - Wall integrated side profile Material:Aluminium 6060, colour:Anodised Aluminum, processing:20 µm anodizing.</p>	<p>Code 98921</p>
		<p>Connector - Fast connector for Ribbon Plus 10mm - Ribbon PRO - Ribbon PRO 48V Length 21,6 mm.</p>	<p>Code 83398</p>




Connector
Length 15,4 mm.

Code
83399



Optics
Light distribution: medium flood,Cover material: pc

Code
C-U100001




Bag / Fixing kit

Code
C-K100027



Bag / Fixing kit

Code
C-K100028



Bag / Fixing kit

Code
C-K100029