



Rubber 3D Optic



LED Strip | 36 topLED 22 W DC 24 V | 22 W/m
2185 Lm/m | CRI 85
82216M20



Technical data	
Length	1000 mm
Minimum cut	168 mm
Type	22 W DC
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	topLED
Optics	Flood
Light emission direction	downward
Nominal power	22 W DC
Source lumens	2185 lm
Input voltage range	24V
CCT / Tone	2700 K
Colour rendering index	85 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP67
IK	IK07
Glow wire test	960°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1(M)x0.25 m + 1(F)x0.25 m
Resin potting	Yes
Type of light emission	Single emission
Length	1000 mm
Net weight	0.29 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing

Material	Technopolymer
Colour	white

Finishing diffuser

Material	PU
Colour	Opal

Electronics

	99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 6 art.)
	99332 1-10V Controller (1 - 6 art.)
	99374 On/Off Driver 198~264V AC / 176~275V DC 75 W (1 - 3 art.)
	83333 Push and Simply Dim - DALI-2 Controller (1 - 6 art.)
	C-E400002 Push and Simply Dim - DALI-2 Controller (1 - 10 art.)

Rubber 3D Optic



LED Strip | 36 topLED 22 W DC 24 V | 22 W/m | 2185 Lm/m | CRI 85 | Base
82216M20



Single emission led strip for outdoor application. The super warm white LED light source with a flood light distribution is composed of 36 topLED LEDs with CCT of 2700 K and a CRI 85; the source luminous flux is 2185 lm, with a 99.3 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu. The ingress protection degree is IP67; the total weight is of 0.29 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 22 W. The power supply cable is included and features a 1(M)x0.25 m + 1(F)x0.25 m length.

The device features protection class III and can be wall lights, ceiling or floor-mounted with an outer casing, code 82199(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	80 %
Source lumens	2185 lm
Delivered lumens	1767 lm
Consumption	22 W
Luminaire efficacy	80 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	85 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature -20 / +50°C

LED Life / Failure Ratio

L70 B20 C0 72500h (at Tj 115 Ta 25)

UGR

UGR axial	20.9
UGR transversal	21.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	17°
C0/C180 optics	28°
Light distribution simmetry	Symmetrical 2 assis

Rubber 3D Optic



LED Strip | 36 topLED 22 W DC 24 V | 22 W/m | 2185 Lm/m | CRI 85 | + 166mm

82216M20

Single emission led strip for outdoor application. The super warm white LED light source with a flood light distribution is composed of 36 topLED LEDs with CCT of 2700 K and a CRI 85; the source luminous flux is 2185 lm, with a 99.3 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu. The ingress protection degree is IP67; the total weight is of 0.29 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 22 W. The power supply cable is included and features a 1(M)x0.25 m + 1(F)x0.25 m length.

The device features protection class III and can be wall lights, ceiling or floor-mounted with an outer casing, code 82199(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	13 %
Source lumens	2185 lm
Delivered lumens	294 lm
Consumption	3.5 W
Luminaire efficacy	84 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	85 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature -20 / +50°C

LED Life / Failure Ratio



L70 B20 C0 72500h (at Tj 115 Ta 25)

UGR

UGR axial	20.9
UGR transversal	21.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	17°
C0/C180 optics	28°
Light distribution symmetry	Symmetrical 2 axis



Rubber 3D Optic



LED Strip | 36 topLED 22 W DC 24 V | 22 W/m | 2185 Lm/m | CRI 85 | + 498mm

82216M20

Single emission led strip for outdoor application. The super warm white LED light source with a flood light distribution is composed of 36 topLED LEDs with CCT of 2700 K and a CRI 85; the source luminous flux is 2185 lm, with a 99.3 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu. The ingress protection degree is IP67; the total weight is of 0.29 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 22 W. The power supply cable is included and features a 1(M)x0.25 m + 1(F)x0.25 m length.

The device features protection class III and can be wall lights, ceiling or floor-mounted with an outer casing, code 82199(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	40 %
Source lumens	2185 lm
Delivered lumens	880 lm
Consumption	11 W
Luminaire efficacy	80 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	85 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature -20 / +50°C

LED Life / Failure Ratio



L70 B20 C0 72500h (at Tj 115 Ta 25)

UGR

UGR axial	20.9
UGR transversal	21.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	17°
C0/C180 optics	28°
Light distribution symmetry	Symmetrical 2 axis





Rubber 3D Optic



LED Strip | 36 topLED 22 W DC 24 V | 22 W/m | 2185 Lm/m | CRI 85
82216M20

Components



D-Wave


Code

77407

Rubber 3D Optic




Rubber 3D Optic | LED Strip | Accessories
82216M20




Outer casing - Linear profile in aluminum 19x18x1000mm for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3d Pixel
installation position: wall lights, ceiling L=1000mm, H=18mm, D=19mm.
Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish	Code
	99549



Outer casing - Linear profile in aluminum 19x18x2000mm for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
installation position: wall lights, ceiling L=2000mm, H=18mm, D=19mm.
Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish	Code
	82198




Profile - Black aluminium 18x19 profile 1m for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
Material:Aluminium, colour:black, processing:Anodisation.

Code
C-K100007




Profile - Black aluminium 18x19 profile 1m for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
Material:Aluminium, colour:black, processing:Anodisation.

Code
C-K100008




Bracket - Clip with toothed spring - Anodised Aluminium - for Rubber 3D (not for Rubber 3D PROtection)
installation position: wall lights, ceiling L=50mm, H=23mm, D=21mm.
Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish	Code
	C-F400001




Bracket - Clip with toothed spring - Anodised Black Aluminium - for Rubber 3D (not for Rubber 3D PROtection)
installation position: wall lights, ceiling L=50mm, H=23mm, D=21mm.
Material:Aluminium, colour:black, processing:Anodisation.

Finish	Code
	C-F400002



Outer casing - Linear profile with aluminium cable passage 39x18x1000mm for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
installation position: wall lights, ceiling L=2000mm, H=39mm, D=19mm.
Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish	Code
	83034




Outer casing - Linear profile with aluminum cable passage 39x18x2000mm for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
installation position: wall lights, ceiling L=1000mm, H=39mm, D=19mm.
Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish	Code
	82199

Rubber 3D Optic




Rubber 3D Optic | LED Strip | Accessories
82216M20




Profile - Profile 39x19 Aluminium black 1m for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
 Material:Aluminium, colour:black, processing:Anodisation.

Code
C-K100009




Profile - Profile 39x19 Aluminium black 2m for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel
 Material:Aluminium, colour:black, processing:Anodisation.

Code
C-K100010




Bracket - Clip with toothed spring with cable passage - Anodised Aluminium - for Rubber 3D (not for Rubber 3D PROtection)
 installation position: wall lights, ceiling L=50mm, H=41mm, D=21mm.
 Material:Aluminium, colour:Aluminium, processing:Anodisation.

Finish
 [Redacted]
Code
C-F400003





Bracket - Clip with toothed spring with cable passage - Anodised Black Aluminium - for Rubber 3D (not for Rubber 3D PROtection)
 installation position: wall lights, ceiling L=50mm, H=41mm, D=21mm.
 Material:Aluminium, colour:black, processing:Anodisation.

Finish
 [Redacted]
Code
C-F400004




Profile - Flexible profile
 Material:AISI 304 steel, colour:steel.

Code
C-K100011




Anti-glare - Anti-glare herringbone eyelid
 Anti-glare Type: eyelid.
 Material:Aluminium 6060, colour:Anodised Aluminum, processing:20 µm anodizing.

Finish
 [Redacted]
Code
C-K100032



Bag / Fixing kit - TILTING KIT + BRACKET D68X20 - Transparent - for Rubber 3D (not Rubber 3D PROtection)

Code
83352




Bag / Fixing kit - Wall-mounted tilting kit in AISI 304 steel

Code
C-K400168

Rubber 3D Optic



Rubber 3D Optic | LED Strip | Accessories
82216M20




Bag / Fixing kit - Wall-mounted tilting kit in AISI 304 steel

Code
C-K400169




Bag / Fixing kit - RUBBER PEG + BRACKET RUBBER PEG + BRACKET PEG + BRACKET D114X204 for Rubber 3D, Rubber 3D Concrete, Rubber 3D 48V, Rubber 3D Optic, Rubber 3D Pixel

Code
83351



Bag / Fixing kit - Picket with tilting bracket

Code
C-F500004




Bag / Fixing kit - Picket with tilting bracket

Code
C-F500005




Closing cap - PU Rubber
Material:Silicone, colour:transparent.

Code
99539




Template

Code
C-V200005



Profile
Material:UV Resistant Polycarbonate, colour:transparent.

Code
C-K100021




Profile
Material:UV Resistant Polycarbonate, colour:transparent.

Code
C-K100022

Rubber 3D Optic




Rubber 3D Optic | LED Strip | Accessories
82216M20



Electronic accessory
installation position: ceiling L=218mm, H=42mm, D=31mm.
Material:ABS Plastic, colour:white.

Code
C-E300007



Electronic accessory
installation position: ceiling L=218mm, H=42mm, D=31mm.
Material:ABS Plastic, colour:black.

Code
C-E300008



Cable gland

Code
98990



Connector

Code
89548



Strip Service - Double sided tape 33 meters

Code
99520