## Archiline\_FJ



## Lines | x powerLEDs 0 W DC - 41 W AC | CRI 80 82307M27






















Technical data





Frameless
Floor
Outdoor
LED
powerLEDs
Asymmetric Wallwasher
upward
0 W DC
41 W
220 - 240 V AC
220 - 240 V AC
2700 K

Finishing casing			
Material	Aluminium 6060		
Colour	Anodised Black		
Processing	15 µm Anodizing		

nmetric	Material	Extra clear glass - Tempered
washer	Colour	transparent
ard	Processing	Silk-screening
DC		

Finishing diffuser

Cables Electrification+signal				
IP (locked condition)	68			
Cable connector	Female Socket 5 Pin			
Cable connector	Male Plug 5 Pin			

Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Asymmetric Wallwasher
Light emission direction	upward
Nominal power	0 W DC
Total Power	41 W
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI
Directional	No
Tilting	Yes
total angle (horizontal plane)	15 °
total angle (vertical plane)	0 °
Walk-over	Yes
Drive-over	5000 Kg
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	4.8 Kg
Electrostatic discharge protection	4 KV
Surge protection	6 KV
Product technological characteristics	Acquastop - TVS

## Archiline\_FJ



Archiline\_FJ | Lines | Accessories **82307M27** 

50 46 821 140 75 1001	Outer casing installation position: floor; type of installation: masonry L=1001mm, H=140mm, D=75m Material:Aluminium 6060, colour:Anodised Black, processing:15 µm Anodizing.	<b>Code</b> 98726
	Cable and connector Length 5000 mm.	<b>Code</b> 99822
	Cable and connector Length 1000 mm.	<b>Code</b> 99823
	Cable and connector Length 5000 mm.	<b>Code</b> 99824
	Cable and connector Length 10000 mm.	<b>Code</b> 99825
	Cable and connector Length 1000 mm.	<b>Code</b> 99826