


Suelo_R Pro



Uplights | x powerLED 0 W DC 24 V | CRI 80
82532N30




Technical data	
Type	Drive Over
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Flood
Light emission direction	upward
Nominal power	0 W DC
Input voltage range	24 V
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP68
Installation limitations	Not for underwater use
IK	IK09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
C.V. - C.C. Converter	Converter 24V included
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	2500 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.15 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Honey comb - Set-back low glare optics
Product technological characteristics	Acquastop - TVS

Finishing casing	
Material	Aluminium 6026
Colour	Anodised Aluminum
Processing	20 µm anodizing
Finishing flange	
Material	OT58 brass
Colour	Raw Brass
Cables Electrification	
Cable connector	No



Suelo_R Pro | Uplights | Accessories
82532N30



Outer casing

installation position: floor, land; type of installation: masonry L=75mm, H=80mm, D=75mm.
Material:ABS Plastic, colour:black.

Code

99684