


# Suelo\_RX Pro



Uplights | 1 x powerLED 3 W DC 24 V | CRI 80  
82541M15



Technical data	
Type	Drive Over
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Spot
Light emission direction	upward
Nominal power	3 W DC
Source lumens	233 lm
Input voltage range	24 V
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP68
Installation limitations	Not for underwater use
IK	IK09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
C.V. - C.C. Converter	Converter 24V included
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	2500 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.16 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Honey comb - Set-back low glare optics
Product technological characteristics	TVS

## Finishing casing

Material	Aluminium 6026
Colour	Anodised Aluminum
Processing	20 µm anodizing

## Finishing flange

Material	OT58 brass
Colour	Raw Brass

## Electronics

	89488 On/Off Driver 190~250V AC / 180~275V DC 15 W (1 - 4 art.)
	89179 On/Off Driver 198~264V AC 24 W (1 - 8 art.)
	89359 On/Off Driver 198~264V AC / 180~275V DC 48 W (1 - 16 art.)
	99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 50 art.)
	99660 DALI - 1-10V Controller 24V DC 216 W (- art.)
	83042 1-10V - Push and Simply Dim - DALI-2 Controller (- art.)



Uplights | 1 x powerLED 3 W DC 24 V | CRI 80 | Base 82541M15


Single emission uplights for outdoor application. The super warm white LED light source with a spot light distribution is composed of 1 powered LED with CCT of 2700 K and a CRI 80; the source luminous flux is 233 lm, with a 77.7 lm/W nominal luminous efficacy.

The device body is made of aluminium 6026 and features a anodised aluminum finish, processed by means of 20 µm anodizing. The ingress protection degree is IP68; the total weight is of 0.16 kg.

The total absorbed power is 3 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99685(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.17 0.17	E(0°) 2266 E(C90) 1097 E(C0) 1086
1.0	0.35 0.34	E(0°) 566 E(C90) 274 E(C0) 272
1.5	0.52 0.51	E(0°) 252 E(C90) 122 E(C0) 121
2.0	0.69 0.68	E(0°) 142 E(C90) 69 E(C0) 68
2.5	0.86 0.85	E(0°) 91 E(C90) 44 E(C0) 43
3.0	1.04 1.03	E(0°) 63 E(C90) 30 E(C0) 30

Distance [m] Cone diameter [m] illuminance [lx]

— C0/C180 (Half-peak divergence: 19.4°)  
— C90/C270 (Half-peak divergence: 19.6°)

## Energy efficiency class

This product contains a light source of energy efficiency class D.

## Illuminotechnical Features

Light Output Ratio (LOR)	44 %
Source lumens	233 lm
Delivered lumens	103 lm
Consumption	3 W
Luminaire efficacy	34 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

## LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25 )

## UGR

UGR axial	19.4
UGR transversal	18.9
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

## OPTICAL

C0/C180 optics	19°
Light distribution simmetry	Symmetrical



Suelo\_RX Pro | Uplights | Accessories  
**82541M15**



Outer casing

installation position: floor, land; type of installation: masonry L=75mm, H=101mm,  
D=75mm.

Material:ABS Plastic, colour:black.

**Code**

99685