
Downlights | x powerLED 0 W DC 350 mA | CRI 90 82739M85





Technical data		
Туре	Encasement with flange	
Installation position	Ceiling	
Installation environment	Indoor	
Light Source	LED	
Circuit structure	powerLED	
Optics	Adjustable Focus	
Light emission direction	downward	
Nominal power	0 W DC	
Input voltage range	350mA	
CCT / Tone	2700 K	
Colour rendering index	90 Ra	
C.C. / C.V.	CC	
Safety class	3	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
	Yes	
Driver included	No	
Dimmable article	DALI - 1-10V	
Directional	Extractable	
total angle (vertical plane)	90 °	
total angle (horizontal plane)	360 °	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	0.2 m	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.1 Kg	
Electrostatic discharge protection	No	
Surge protection	No	

En ce 🕱 🕐 🖻 🗑 cc. 🖂 🕫 🗋



Finishing casing

Material	Die-cast Aluminium EN AB - 46100
Colour	White
Processing	Powder coating
Flocessing	Fowder coaling

No

Cables Electrification

Cable connector