Vedette_R Double emission



Wall Lights | x powerLED 0 W DC - 9 W AC | CRI 80 82780M30





Technical data				
Туре	Surface			
Installation position	Wall lights			
Installation environment	Outdoor			
Light Source	LED			
Circuit structure	powerLED			
Optics	Double Medium Flood			
Light emission direction	downward and upward			
Nominal power	0 W DC			
Total Power	9 W			
Nominal input voltage	220 - 240 V AC			
Input voltage range	198 - 264 V AC			
CCT / Tone	2700 K			
Colour rendering index	80 Ra			
C.C. / C.V.	AC			
Safety class	2			
IP	IP66			
IK	IK05			
Glow wire test	850°			
Direct mounting on normally flammable surfaces	Yes			
CE	Yes			
Driver included	Driver			
Dimmable article	No			
Directional	No			
Tilting	No			
Walk-over	No			
Drive-over	No			
Cable included	Yes			
Cable length	1 m			
Resin potting	Yes			
Type of light emission	Double emission			
Net weight	0.31 Kg			
Electrostatic discharge protection	Yes			



Processing




















Finishing casing					
Material	Die-cast Aluminium EN AB - 46100				
Colour	Grey				
Processing	Open pore anodizing + Powder Coating	pen pore anodizing + Powder Coating			
Finishing diffuse	r				
Material	Extra clear glass - Tempered				
Colour	opaline				

Cables Electrifica	tion			
Cable connector	No			

Sandblasting

Acquastop - TVS

Product technological characteristics