Vedette_R Double emission




Wall Lights | arrayLED 0 W DC - 18 W AC | CRI 80 82798M60





Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Double Wide Flood	
Light emission direction	downward and upward	
Nominal power	0 W DC	
Total Power	18 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	198 - 264 V AC	
CCT / Tone	2700 K	
Colour rendering index	80 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP65	
IK	IK07	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	1 m	
Resin potting	No	
Type of light emission	Double emission	
Net weight	0.96 Kg	
Electrostatic discharge protection	Yes	
Surge protection	1 KV	
B. 1. (1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		





Finishing casing	
Material	Die-cast Aluminium EN AB - 46100
Colour	White
Processing	Open pore anodizing + Powder Coating
Cables Electrifica	tion
Cable connector	No

Acquastop

Product technological characteristics