




# Vedette\_R Double emission



Wall Lights | arrayLED 0 W DC - 30 W AC | CRI 80  
82821N00



| Technical data                                 |                     |
|--|---------------------|
| Type   | Surface             |
| Installation position                          | Wall lights         |
| Installation environment                       | Outdoor             |
| Light Source                                   | LED                 |
| Circuit structure                              | arrayLED            |
| Optics   | Double Diffused     |
| Light emission direction                       | downward and upward |
| Nominal power                                  | 0 W DC              |
| Total Power                                    | 30 W                |
| Nominal input voltage                          | 220 - 240 V AC      |
| Input voltage range                            | 198 - 264 V AC      |
| CCT / Tone                                     | 4000 K              |
| Colour rendering index                         | 80 Ra               |
| C.C. / C.V.                                    | AC                  |
| Safety class                                   | 1                   |
| IP   | IP65                |
| IK   | IK06                |
| Glow wire test                                 | 850°                |
| Direct mounting on normally flammable surfaces | Yes                 |
| CE   | Yes                 |
| Driver included                                | Driver              |
| Dimmable article                               | No                  |
| Directional                                    | No                  |
| Tilting  | No                  |
| Walk-over                                      | No                  |
| Drive-over                                     | No                  |
| Cable included                                 | Yes                 |
| Cable length                                   | 1 m                 |
| Resin potting                                  | No                  |
| Type of light emission                         | Double emission     |
| Net weight                                     | 1.75 Kg             |
| Electrostatic discharge protection             | Yes                 |
| Surge protection                               | 1 KV                |
| Product technological characteristics          | Acquastop - TVS     |

| Finishing casing       |                                      |
|------------------------|--------------------------------------|
| Material               | Die-cast Aluminium EN AB - 46100     |
| Colour                 | Dark brown                           |
| Processing             | Open pore anodizing + Powder Coating |
| Cables Electrification |                                      |
| Cable connector        | No                                   |