




Wall Lights - Ceiling Downlights | 220-240 V | 1xGX53  
8321



64

Ø92

Technical data	
Construction year	2019
Type	Surface - Surface
Installation position	Wall lights - Ceiling
Installation environment	Outdoor
Lamp cap	1 x GX53 Max 4W
Light emission direction	frontal + frontal
Frequency	50-60 Hz
Optics	Diff. + Diff.
Safety class	2
IP	IP65
IK	IK06
Glow wire test	850°
Direct mounting on normally flammable surfaces	No
CE	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	0.170 Kg

Finishing casing	
Material	UV Resistant Polycarbonate
Colour	White
Processing	Liquid painting

Finishing diffuser	
Material	Silicone
Colour	transparent
Processing	Satin finishing

Finishing mounting frame	
Material	Iron
Colour	zinc
Processing	Washing

## Wall Lights - Ceiling Downlights | 220-240 V | 1xGX53 | Base 8321

Double emission wall lights or ceiling downlights for outdoor application.

Compatibility: LED lamp; lamp cap 1xGX53.

The device body is made of uv resistant polycarbonate and features a white finish, processed by means of liquid painting; the diffuser is made of silicone with a satin finishing treatment; the mounting frame is made of iron, with a zinc finish, processed by means of washing. The ingress protection degree is IP65; the total weight is of 0.170 kg.

The device features protection class II and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	100 %
Source lumens	500 lm
Delivered lumens	152 lm
Consumption	4 W
Luminaire efficacy	38 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	
	-20 / +50°C

LED Life / Failure Ratio	
<b>UGR</b>	
UGR axial	24.9
UGR transversal	24.7
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
C0/C180 optics	180°
Light distribution simmetry	Symmetrical

