


Astropek_2 Blade V2



Uplights | 2 x powerLEDs 4 W DC 630 mA | CRI 80
83522W05



Technical data	
Type	Surface - -
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Ultra Spot
Light emission direction	external
Nominal power	4 W DC
Source lumens	568 lm
Input voltage range	630mA
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	2500 Kg
Cable included	Yes
Cable length	3 m
Resin potting	Yes
Type of light emission	Double emission
Net weight	0.85 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop

Finishing casing

Material	Aluminium
Colour	grey RAL 9006
Processing	Coating


Finishing diffuser


Material	Glass
Colour	white
Processing	Sandblasting


Finishing base

Material	PC
Colour	grey

Electronics

 89420
On/Off Driver 198~264V AC / 176~275V DC (1 art.)

 99186
On/Off Driver 198~264V AC (3 - 6 art.)

 C-E200008
On/Off Driver 198~264V AC / 180~275V DC (1 - 3 art.)

Astropek_2 Blade V2



Uplights | 2 x powerLEDs 4 W DC 630 mA | CRI 80 | Base
83522W05

Double emission uplights for outdoor application. The warm white LED light source with a ultra spot light distribution is composed of 2 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 568 lm, with a 142.0 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP67; the total weight is of 0.85 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4 W. The power supply cable is included and features a 3 m length.

The device features protection class III and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 2 light sources of energy efficiency class D.

Illuminotechnical Features

Light Output Ratio (LOR)	5 %
Source lumens	568 lm
Delivered lumens	33 lm
Consumption	4 W
Luminaire efficacy	8 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	1.5 Step
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	50°C

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)

OPTICAL

C0/C180 optics	180°
Light distribution symmetry	Symmetrical

