Astropek_1 Blade V2



Uplights | x powerLEDs 0 W DC 630 mA | CRI 92 83524N05





Colour






















Technical data		
Туре	Surface	
Installation position	Floor	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	powerLEDs	
Optics	Ultra Spot	
Light emission direction	external	
Nominal power	0 W DC	
Input voltage range	630mA	
CCT / Tone	4000 K	
Colour rendering index	92 Ra	
C.C. / C.V.	CC	
Safety class	3	
IP	IP67	
IK	IK10	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	DALI - 1-10V	
Directional	No	
Tilting	No	
Walk-over	Yes	
Drive-over	2500 Kg	
Cable included	Yes	
Cable length	3 m	
Resin potting	Yes	
Type of light emission	Single emission	
Net weight	0.85 Kg	
Electrostatic discharge protection	No	
Surge protection	No	
Product technological characteristics	Acquastop	

Finishing casing			
Material	Aluminium		
Colour	grey RAL 9006		
Processing	Coating		
Finishing diffus	er		
Material	Glass		

_	
Material	Glass
Colour	white
Processing	Sandblasting
Finishing base	
Material	PC

grey