

# Beret\_2Q



Uplights | 198-264 V AC /186-275 V DC  
1 x powerLED 1.6 W DC - 3 W AC | CRI 80

**83710M08**



Technical data	
Type	Frame
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Narrow Spot
Light emission direction	upward
Nominal power	1.6 W DC
Total Power	3 W
Source lumens	233 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP67
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	2000 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.180 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV
Product technological characteristics	Acquastop

Finishing casing	
Material	OT58 brass
Colour	Raw Brass



Uplights | 198-264 V AC /186-275 V DC | 1 x powerLED 1.6 W DC - 3 W AC | CRI 80 | Base  
**83710M08**

Single emission uplights for outdoor application. The super warm white LED light source with a narrow spot light distribution is composed of 1 powered LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 233 lm, with a 145.6 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a raw brass finish. The ingress protection degree is IP67; the total weight is of 0.180 kg.

The total absorbed power is 3 W. The power supply cable is included and features a 1 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 84918(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class D.

### Illuminotechnical Features

Light Output Ratio (LOR)	64 %
Source lumens	233 lm
Delivered lumens	150 lm
Consumption	3 W
Luminaire efficacy	50 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Colour rendering index	80 Ra
<b>Standard Operating Ambient Temperature</b> -20 / +50°C	
<b>Ordinary temperature on the glass</b> 50°C	

### LED Life / Failure Ratio


L70 B10 C0 361980h (at Tj 60 Ta 25 )

### UGR

UGR axial	11.6
UGR transversal	11.7
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	10°
Light distribution simmetry	Symmetrical



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.09 0.09	E(0°) 7175 E(C90) 5.1° 3564 E(C0) 5.2° 3600
1.0	0.18 0.18	E(0°) 1794 E(C90) 5.1° 891 E(C0) 5.2° 900
1.5	0.27 0.27	E(0°) 797 E(C90) 5.1° 396 E(C0) 5.2° 400
2.0	0.36 0.36	E(0°) 448 E(C90) 5.1° 223 E(C0) 5.2° 225
2.5	0.45 0.46	E(0°) 287 E(C90) 5.1° 143 E(C0) 5.2° 144
3.0	0.54 0.55	E(0°) 199 E(C90) 5.1° 99 E(C0) 5.2° 100

— C0/C180 (Half-peak divergence: 10.4°)  
 — C90/C270 (Half-peak divergence: 10.2°)



Beret\_2Q | Uplights | Accessories  
**83710M08**



Outer casing

installation position: floor, land; type of installation: masonry L=87mm, H=60mm, D=60mm.

Material:ABS Plastic, colour:black.

**Code**

84918